SOUTHERN PACIFIC COMPANY

(PACIFIC LINES)

TIME TABLE

FOR THE

SAN JOAQUIN DIVISION

155

To Take Effect Sunday, February 2, 1936, at 12:01 A. M.

PACIFIC STANDARD TIME (120th MERIDIAN)

For the government and information of employes only.

A. T. MERCIER,
General Manager.

W. B. KIRKLAND,
Superintendent of Transportation.

L. U. MORRIS,
Assistant General Manager.

J. D. BRENNAN,
Superintendent.

		EASTWARD											WESTWARD								
		SECOND CLASS	FIRST CLASS								Time Table No. 155 February 2, 1936		FIRST CLASS								
Capacity of Sidings in Car Lengths		400	26	56	346	52	10	58	60	Distance from San Francisco		Distance from Bakersfield	25	59	55	345	5	51	57		
		Freight	Owl	Tehachapi	Motor	San Joaquin	Santa Fe Motor	Sequoia	West Coast				Owl	West Coast	Tehachapi	Motor	Santa Fe Motor	San Joaquin	Sequoia		
		Leave Daily	Leave Daily	Leave Daily	Leave Daily	Leave Daily	Leave Daily	Leave Daily	Leave Daily		**STATIONS**		Arrive Daily	Arrive Daily	Arrive Daily	Arrive Daily	Arrive Daily	Arrive Daily	Arrive Daily		
WOTYP Yard										201.8	FRESNO YARD 1.4	111.1									
										203.2	F. T. Co. Crossing 2.3 Double Track	109.7									
BKWOTYP Yard		4.20 AM	11.45 PM	8.00 PM		1.55 PM		7.20 AM	12.30 AM	205.5	TO-R FRESNO 3.6	107.4	s 2.33 AM	4.10 AM	7.45 AM			s 4.00 PM	s 10.00 PM		
I P		4.30	11.55 PM	8.10		2.05		**7.33**	12.40	209.1	TO CALWA TOWER A. T. & S. F. Crossing 1.3	103.8	2.23	4.00	**7.33**			3.50	9.48		
P				f				s		210.4	MALAGA 4.7	102.5			f						
118 P		4.40		f 8.20		2.13		s 7.41		215.1	TO FOWLER 5.6	97.8			f 7.20			3.41	f 9.39		
125 Yard WP		4.50	f 12.11 AM	s 8.30		f 2.21		s 7.51	12.54	220.7	TO SELMA 4.9	92.2	f 2.07	3.44	s 7.08			f 3.32	s 9.31		
100 Yard WP		5.00	12.18	s 8.40		f 2.30		s 8.01	1.00	225.6	TO KINGSBURG 5.7	87.3	1.59	3.36	s 6.56			f 3.22	s 9.22		
106 P		5.09	12.25	f 8.48		2.37		8.08		231.3	TRAVER 2.4	81.6		3.29	f 6.44			3.14	9.13		
P			12.28	8.51		2.40		8.11		233.7	CROSS 5.4	79.2		3.26	6.41			3.11	9.10		
94 WOYP Yard		5.21	12.35	s **9.00**		s 2.47		s 8.18 AM	1.16	239.1	TO-R GOSHEN JCT. 6.5	73.8	1.43	3.19	s 6.31			s 3.04	**9.00 PM**		
59 P		5.31	12.42	f 9.18		**2.55**			1.23	245.6	TAGUS 4.1	67.3	1.36	3.11	6.11			**2.55**			
										249.7	TO TULARE TOWER A. T. & S. F. Crossing 0.3	63.2									
89 WP		**5.48**	s 12.51	s 9.25		s 3.07			**1.29**	250.0	TULARE 5.8	62.9	s **1.29**	3.03	s **5.48**			s 2.48			
59 P		5.58	12.59	9.45		3.16			1.40	255.8	OCTOL 4.6	57.1	1.17		5.41			2.39			
83 WP		6.05	**1.10**	s 10.05		f 3.22			1.45	260.4	A. B. S. TO TIPTON 6.4	52.5	**1.10**	2.50	s 5.29			2.34			
94 P		6.15	1.19	s 10.15		3.29			1.52	266.8	TO PIXLEY 5.6	46.1	1.03	2.43	s 5.21			2.27			
83 P				f 10.25		3.35			1.58	272.4	TO EALIMART 4.1	40.5	12.57	2.37	s 5.11						
59 P		6.30	1.30	10.31						276.5	RADNOR 4.2	36.4		2.32	5.02			2.17			
82 WP		6.37	1.36	s 10.40		s 3.44			2.09	280.7	TO DELANO 6.3	32.2	f 12.47		s 4.56			s 2.12			
59 P		6.47	1.44	s 10.50		3.52			**2.16**	287.0	TO Mc FARLAND 5.6	25.9	12.39	**2.16**	s 4.45			2.04			
79 KWTP		**7.00**	1.50	f 10.59	10.42 PM	3.58	9.26 AM		2.26	292.6	TO-R FAMOSO 3.3	20.3	12.33	2.09	f 4.35	s **7.00 AM**	s 12.19 PM	1.58			
59 P		7.05		11.03	f 10.48		9.32			295.9	SLATER 4.6	17.0			4.29	6.56	12.14	1.54			
82 P		7.12	**1.59**	11.09	f 10.54	4.06	9.39		2.35	300.5	LERDO 2.5	12.4	12.24	**1.59**	4.24	f 6.51	12.07	1.49			
90 P		7.16	2.04	11.12	10.58	4.09	9.44		2.38	303.0	PROSPERO 2.8	9.9	12.21	1.56	4.21	6.48	12.03 PM	1.46			
59 P		7.21		11.15	f 11.01		9.49			305.8	SACO 2.8	7.1			4.18	6.44	11.59 AM	1.43			
80 P		7.26	2.10	11.19	11.04	4.15	s 9.54 AM		2.44	308.6	R OIL JCT. 2.5	4.3	12.15	1.50	4.15	f 6.40	11.54 AM	1.40			
P										311.1	NOME 1.8	1.8									
Yard BKWOTYP		7.40 AM	s 2.20 AM	s 11.30 PM	s 11.15 PM	s 4.25 PM			s 2.54 AM	312.9	TO-R BAKERSFIELD	0.0	12.05 AM	1.40 AM	4.05 AM	6.30 AM		1.30 PM			
		Arrive Daily	Arrive Daily	Arrive Daily	Arrive Daily	Arrive Daily	Arrive Daily	Arrive Daily	Arrive Daily		(111.1)		Leave Daily	Leave Daily	Leave Daily	Leave Daily	Leave Daily	Leave Daily	Leave Daily		
		(3.20) 32.22	(2.35) 41.57	(3.30) 30.66	(0.33) 36.90	(2.30) 42.96	(0.28) 34.28	(0.58) 34.74	(2.24) 44.75		Time over District Average Speed per Hour		(2.28) 43.54	(2.30) 42.96	(3.40) 29.29	(0.30) 40.60	(0.25) 38.40	(2.30) 42.96	(1.00) 33.60		

Schedule time and train orders for eastward trains at Calwa Tower apply at end of double track, 360 feet west of the tower.

Rule S-72 Exception; No. 56 is superior to No. 57.

Schedule time and train orders for eastward trains at Famoso apply at junction switch of Porterville Line.

Schedule time and train orders for trains at Oil Jct. apply at crossover switch just west of Signal 3086.

ADDITIONAL STATIONS:

Calwa	208.3
Winedale (Spur)	222.8
Midvalley (Spur)	243.4
Burling (Spur)	251.5
Alfac (Spur)	262.3
Quail (Spur)	263.7
Stone (Spur)	275.8
Dow (Spur)	299.6

ADDITIONAL FLAG STOPS TO RECEIVE OR DISCHARGE PASSENGERS

Train	At	Receive or Discharge	To (or beyond)	From (or beyond)	Frequency
60	Selma	Discharge		Stockton	Daily
60	Tulare	Discharge		Stockton	Daily
60	Delano	Discharge		Stockton	Daily
56	Any Station	Discharge		Delano	Daily
55	Any Station	Discharge		Los Angeles	Daily
52	Any Station	Discharge		Ogden	Daily
26	Delano	Receive and Discharge	Los Angeles	Tracy	Daily

EASTWARD — FRESNO SUBDIVISION — WESTWARD

Capacity of Sidings in Car Lengths	FIRST CLASS				Distance from San Francisco		Time Table No. 155 February 2, 1936	Distance from Famoso	FIRST CLASS			
	346	348	10	58					345	5	347	57
	Motor	Motor	Santa Fe Motor	Sequoia					Motor	Santa Fe Motor	Motor	Sequoia
	Leave Daily	Leave Daily	Leave Daily	Leave Daily			STATIONS		Arrive Daily	Arrive Daily	Arrive Daily	Arrive Daily
BKWOTYP Yard	7.15PM				205.5		TO-R FRESNO	104.3	s 10 20AM			
							1.5					
I					207.0		TO SUNMAID TOWER A. T. & S. F. Crossing	102.8				
							1.5					
	7.26				208.5		BLOSSOMA	101.3	f 10.08			
							3.3					
15 P	7.30				211.8		BUTLER	98.0	f 10.03			
							1.2					
PY					213.0		LOCANS	96.8	f			
							1.5					
18	7.34				214.5		IVESTA	95.3	f 9 59			
							1.4					
77 P	f 7.36				215.9		CLOTHO	93.9	f 9.56			
							3.9					
90 Yard WP	s 7.44				219.8		TO SANGER	90.0	s 9.50			
							3.0					
8 P	f 7.48				222.8		TARN	87.0	f 9.42			
							2.5					
P	f 7.52				225.3		FARGO	84.5	f 9.38			
							2.6					
	f 7.56				227.9		LACJAC	81.9	f 9.34			
							0.1					
					228.0		A. T. & S. F. Crossing (Stop)	81.8				
							1.9					
85 Yard P	s 8.02				229.9		TO REEDLEY	79.9	s 9.28			
							5.1					
63 Yard WP	s 8.11				235.0		TO DINUBA	74.8	s 9 18			
							2.2					
P	f				237.2		SMYRNA	72.6	f			
							2.4					
67 P	f 8.18				239.6		MONSON	70.2	f 9.08			
							4.0					
					243.6		A. T. & S. F. Crossing (Stop)	66.2				
							2.8					
18 P	8.30				246.4		TAURUSA	63.4	f 8.56			
							3.0					
14	s 8.37				249.4		TO IVANHOE	60.4	s 8.51			
							2.8					
P	f 8.41				252.2		ROCHE	57.6	f 8.46			
							0.9					
18 P	8.43				253.1		CAPLIN	56.7	f 8.44			
							4.3					
74 KWYP Yard	s 8.55	3.55PM		9.10AM	257.4	Block Signals	TO-R EXETER	52.4	s 8.35		s 1.50PM	s 7.50PM
							3.1					
8	f 9.00	4.00		9.15	260.5		BURR	49.3	8.25		1.44	7.44
							3.8					
124 P Yard	s 9.10	s 4.08		s 9.23	264.3		TO LINDSAY	45.5	s 8.20		s 1.38	s 7.38
							4.3					
32 P	s 9.18	f 4.15		s 9.30	268.6		TO STRATHMORE	41.2	s 8.10		f 1.28	f 7.28
							2.3					
7	f				270.9		ZANTE	38.9				
							3.5					
14 P	s 9.35	s 4.25		s 9.40	274.4		PORTERVILLE	35.4	s 8.00		s 1.20	s 7.20
							0.4					
42 BKWYP Yard	9.39	4.40PM		9.55AM	274.8		TO-R PORTERVILLE-OLIVE ST.	35.0	7.57		1.10PM	7.10PM
							1.7					
13	9.43				276.5		PONCA	33.3	7.54			
							1.5					
25	f				278.0		LOIS	31.8	f			
							4.6					
17 P	s 9.53				282.6		TO TERRA BELLA	27.2	f 7.45			
							4.5					
69 KP	s 10.02		8.45AM		287.1		TO-R DUCOR	22.7	f 7.38	s 1.00PM		
							2.9					
17 P	f 10.07		8.51		290.0		ORRIS	19.8	f 7.32	12.54		
							1.5					
Spur	f		f		291.5		VESTAL	18.3	f	f		
							3.4					
67 YP	f 10.15		f 8.59		294.9		RICHGROVE	14.9	f 7.25	f 12.46		
							4.1					
18 P	f 10.22		f 9.06		299.0		JASMIN	10.8	f 7.19	f 12.39		
							10.8					
4 KWTP	s 10.40PM		s 9.23AM		309.8		TO-R FAMOSO	0.0	7.03AM	12.22PM		
							(104.3)					
	Arrive Daily	Arrive Daily	Arrive Daily	Arrive Daily					Leave Daily	Leave Daily	Leave Daily	Leave Daily
	(3.25) 30.52	(0.45) 23.20	(0.38) 35.84	(0.45) 23.20			……Time over District…… ……Average Speed per Hour……		(3.17) 31.76	(0.38) 35.84	(0.40) 26.10	(0.40) 26.10

ADDITIONAL STATIONS:

Goldleaf 209.9	Efco (Spur) 227.6	Stout (Spur) 265.8
Eshel (Spur) 210.6	Dorsey (Spur) 250.8	Lisko (Spur) 272.2
Reka 221.0	Lort (Spur) 254.0	Quality (Spur) 295.9
Rusconi (Spur) 221.8	Vance 262.8	
Uva (Spur) 227.1		

No. 347 and No. 57 head in at east end of siding at Exeter and use siding to junction of Visalia Branch.

TEHACHAPI SUBDIVISION

	EASTWARD										Time Table No. 155			WESTWARD							
	SECOND CLASS				FIRST CLASS						February 2, 1936			FIRST CLASS					THIRD CLASS		
Capacity of Sidings in Car Lengths	816	814	812	810	56	2	52	60	26	Distance from San Francisco	STATIONS		Distance from Mojave	55	23	51	25	59	811	813	815
	Freight	Freight	Freight	Freight	Tehachapi	Santa Fe Passenger	San Joaquin	West Coast	Owl					Tehachapi	Santa Fe Passenger	San Joaquin	Owl	West Coast	Freight	Freight	Freight
	Leave Daily	Leave Daily	Leave Daily	Leave Daily	Leave Daily	Leave Daily	Leave Daily	Leave Daily	Leave Daily					Arrive Daily	Arrive Daily	Arrive Daily	Arrive Daily	Arrive Daily	Arrive Daily	Arrive Daily	Arrive Daily
BKWOTYP Yard					11.50PM		4.33PM	3.04AM	2.30AM	312.9	TO-R BAKERSFIELD 0.7	A.B.S.	67.8	s 3.50AM		s 1.20PM	s 11.55PM	1.30AM			
KI P	6.30PM	11.55AM	6.05AM	12.01AM	**11.52PM**	7.20PM	4.36	3.07	2.33	313.6	TO-R KERN JCT. 3.4	Double Track	67.1	3.47	11.35AM	1.17	**11.52**	1.27	8.55AM	6.00PM	2.40AM
No Siding P										317.0	MAGUNDEN 3.1		63.6								
50 P					f					320.1	EDISON 7.8		60.6	f							
80 IP	7.00	12.25PM	6.30	12.26	12.15AM	7.39	4.55	3.27	2.52	327.9	BENA 3.4		52.8	3.23	11.13	12.58	11.30	1.05	8.22	5.31	2.15
85 P	7.08	12.33	6.38	12.34	12.21	7.44	5.00	3.33	2.58	331.3	ILMON 3.9		49.4	3.17	11.08	12.53	11.24	12.59	8.12	5.21	2.05
East 68 West 68 IWP	7.18	**12.45**	6.50	**12.49**	s 12.31	7.52	f **5.09**	3.42	**3.07**	335.2	TO CALIENTE 3.0		45.5	s **3.07**	f 10.59	f **12.45**	11.15	**12.49**	8.00	**5.09**	1.53
82 P					**12.42**					338.2	ALLARD 2.3		42.5	2.57	10.51	12.37	11.08	**12.42**	7.50	4.45	1.44
West 71 East 71 IWP										340.5	TO BEALVILLE 1.8		40.2								
71 IP	7.40	1.13	7.17	1.14	12.53	8.09	5.26	3.59	3.24	342.8	CLIFF 3.2		38.4								
East 73 West 73 P	7.50	1.23	**7.27**	**1.26**	1.00	8.16	5.33	4.06	3.31	345.5	ROWEN 3.3		35.2	2.41	10.35	12.21	10.52	12.26	**7.27**	4.27	**1.26**
123 IWP House 66	8.10	1.45	7.55	1.41	s **1.09**	8.24	f 5.41	4.15	3.40	348.8	TO WOODFORD 3.0		31.9	s 2.34	10.28	f 12.14	10.44	12.18	7.17	4.17	**1.09**
99 P	**8.31**	2.00	8.10	1.56	1.17	**8.31**	5.48	4.22	3.47	351.8	WALONG 2.3		28.9	2.27	10.21	12.07	10.37	12.11	7.07	4.07	12.57
West 69 East 69 IWP	8.45	2.10	8.21	2.06	1.24	8.37	5.54	4.28	3.53	354.1	MARCEL 2.6		26.6	2.22	10.16	12.02PM	10.31	12.05AM	7.00	4.00	12.50
81 P	8.55	2.20	8.32	**2.16**	1.32	8.45	6.02	4.35	4.00	356.7	CABLE 3.9		24.0	**2.16**	10.10	11.56AM	10.25	11.59PM	6.52	3.52	12.42
IWP 100 Yard	9.14	2.35	8.45	2.35	s 1.43	f 8.55	s 6.12	4.44	4.10	360.6	TO-R TEHACHAPI 1.8	Double Track	20.1	s 2.07	s 10.01	s 11.47	10.15	11.50	6.40	3.40	12.30AM
100 YP					1.47	8.59	6.16	4.48	4.14	362.4	SUMMIT SWITCH 2.6		18.3	2.01	9.58	11.44	10.11	11.47			
70 P					f 1.52	9.03	f 6.21	4.53	4.18	365.0	MONOLITH 3.0		15.7	s 1.56	9.54	f 11.40	10.06	11.43			
YP Yard										368.0	ERIC 1.9		12.7								
WP					1.59	9.10	6.28	4.59	4.24	369.9	CAMERON 4.4		10.8	f 1.47	9.47	11.32	9.58	11.35			
78 P					2.07	9.18	6.36	5.06	4.31	374.3	WARREN 6.4		6.4	1.37	9.37	11.23	9.48	11.26			
Yard BKWOTYP	10.25PM	3.45PM	9.55AM	3.55AM	s 2.20AM	s **9.32PM**	s 6.49PM	5.20AM	s 4.45AM	380.7	TO-R MOJAVE		0.0	1.20AM	9.20AM	11.07AM	**9.32PM**	11.10PM	5.40AM	2.40PM	11.30PM
	Arrive Daily	Arrive Daily	Arrive Daily	Arrive Daily	Arrive Daily	Arrive Daily	Arrive Daily	Arrive Daily	Arrive Daily		(67.8)			Leave Daily	Leave Daily	Leave Daily	Leave Daily	Leave Daily	Leave Daily	Leave Daily	Leave Daily
	(3.55) 17.13	(3.50) 17.50	(3.50) 17.50	(3.54) 17.17	(2.30) 27.12	(2.12) 30.50	(2.16) 29.91	(2.16) 29.91	(2.15) 30.13		Time over District Average Speed per Hour			(2.30) 27.12	(2.15) 29.82	(2.13) 30.58	(2.23) 28.24	(2.20) 29.05	(3.15) 20.64	(3.20) 20.13	(3.10) 21.18

Schedule time and train orders at Tehachapi apply at end of double track.

MOJAVE SUBDIVISION

EASTWARD / WESTWARD

Time Table No. 155

February 2, 1936

	EASTWARD SECOND CLASS		FIRST CLASS									WESTWARD FIRST CLASS				THIRD CLASS		
Capacity of Sidings in Car Lengths	816 Freight	814 Freight	810 Freight	52 San Joaquin	60 West Coast	26 Owl	56 Tehachapi	Distance from San Francisco		STATIONS		Distance from Saugus	51 San Joaquin	25 Owl	59 West Coast	55 Tehachapi	811 Freight	813 Freight	815 Freight
	Leave Daily	Leave Daily	Leave Daily	Leave Daily	Leave Daily	Leave Daily	Leave Daily						Arrive Daily	Arrive Daily	Arrive Daily	Arrive Daily	Arrive Daily	Arrive Daily	Arrive Daily
BKWOTYP Yard	11.25PM	4.50PM	4.40AM	6.52PM	**5.25AM**	4.55AM	2.40AM	380.7	A.B.S.	TO-R	MOJAVE 4.1	69.9	s 11.04AM	s 9.22PM	11.06PM	s 1.05AM	**5.25AM**	1.40PM	10.30PM
84 P	11.35	5.00	4.50	6.58	5.31	5.01	2.46	384.8			FLETA 2.5	65.8	10.58	9.16	11.00	12.59	5.15	1.25	10.16
85 P	11.40	5.05	**5.05**	7.01	5.35	**5.05**	2.50	387.3			GLOSTER 3.1	63.3	10.55	9.12	10.56	12.55	**5.05**	1.15	10.11
81 P	11.46	5.11	5.15	7.05	5.40	5.10	2.55	390.4			ANSEL 3.9	60.2	10.51	9.07	10.51	12.50	4.53	1.06	10.03
80 P	11.53PM	5.18	5.25	7.10	5.46	5.16	f 3.01	394.3			ROSAMOND 5.6	56.3	10.46	9.01	10.45	f 12.44	4.46	12.58	9.56
50 P	12.05AM	5.28	5.35	7.17	5.54	5.24	3.09	399.9			OBAN 5.6	50.7	10.39	8.53	10.37	12.34	4.36	12.48	9.46
70 KWP Yard	**12.25**	5.45	5.50	s 7.25	6.02	5.32	s 3.19	405.5		TO-R	LANCASTER 4.3	45.1	s 10.31	f 8.45	10.28	s **12.25**	4.26	12.38	9.36
50 P	12.43	6.00	**6.08**	7.32	**6.08**	5.38	3.26	409.8			DENIS 4.0	40.8	10.25	8.34	10.18	12.10	4.18	12.29	9.28
68 P WOY P	12.51	6.08	6.28	f 7.38	6.13	5.43	s 3.34	413.8		TO	PALMDALE 2.5	36.8	f 10.20	8.29	10.13	s 12.04AM	4.10	12.21	9.20
90 P	12.58	6.15	6.35	7.42	6.17	5.47	3.39	416.3			HAROLD 4.2	34.3	10.16	8.25	10.09	11.55PM	4.04	12.14PM	9.13
East 75 Yard West 81 YP	1.20	6.45	7.00	7.54	6.29	5.59	**3.51**	420.5			VINCENT 4.5	30.1	10.07	8.16	10.00	11.46	**3.51**	11.59AM	9.00
84 P	1.34	6.59	7.19	**8.06**	6.39	6.09	4.01	425.0			PARIS 1.1	25.6	9.57	**8.06**	9.50	11.35	3.22	11.32	8.35
32 P							f 4.04	426.1			ACTON 2.9	24.5				f 11.32			
95 WP	1.50	7.21	7.41	**8.18**	6.48	6.18	f 4.12	429.0			RAVENNA 5.6	21.6	9.48	7.57	9.41	f 11.23	3.09	11.19	**8.18**
82 P	2.15	**7.45**	7.58	8.31	7.00	6.30	4.24	434.6			RUSS 4.2	16.0	9.36	**7.45**	9.29	11.10	2.52	11.02	**7.45**
101 WP	**2.39**	8.05	8.11	8.41	7.09	6.39	f 4.34	438.8		TO	LANG 4.3	11.8	9.27	7.36	9.20	f 10.59	**2.39**	10.49	7.19
85 P	2.53	8.18	8.24	8.52			4.45	443.1			HUMPHREYS 3.8	7.5				f 10.49	2.27	10.37	7.07
81 P	3.05	8.30	8.36	**9.02**	7.27	6.57	4.55	446.9			HONBY 3.7	3.7	9.10	7.18	**9.02**	10.40	2.16	10.26	6.56
W 78 E 71 BKWOY Yard P	3.20AM	**8.50PM**	8.50AM	s 9.12PM	7.35AM	7.05AM	s 5.04AM	450.6		TO-R	SAUGUS	0.0	9.02AM	7.10PM	**8.50PM**	10.32PM	2.05AM	10.15AM	6.45PM
	Arrive Daily	Arrive Daily	Arrive Daily	Arrive Daily	Arrive Daily	Arrive Daily	Arrive Daily				69.9		Leave Daily	Leave Daily	Leave Daily	Leave Daily	Leave Daily	Leave Daily	Leave Daily
	(3.55) 17.84	(4.00) 17.47	(4.10) 16.77	(2.20) 29.95	(2.10) 32.26	(2.10) 32.26	(2.24) 29.12				Time over District Average Speed per Hour		(2.02) 34.37	(2.12) 31.77	(2.16) 30.84	(2.33) 27.41	(3.20) 20.97	(3.25) 20.45	(3.45) 18.64

At Saugus: San Joaquin Division time table schedules and train orders apply at the east switch of the eastward siding.
Los Angeles Division time table schedules and train orders apply at the Junction switch of the Santa Paula Line.
The main track at Saugus between the Junction switch and east switch of the eastward siding may be used by any train, if track is known to be clear. Care must be taken not to delay first-class trains

ADDITIONAL FLAG STOPS TO RECEIVE OR DISCHARGE PASSENGERS

Train	At	Receive or Discharge	To (or beyond)	From (or beyond)	Frequency
26	Lancaster	Receive	Glendale		Daily
26	Palmdale	Receive	Glendale		Daily
59	Lancaster	Receive	Stockton		Daily
60	Lancaster	Discharge		Stockton	Daily

FRESNO SUBDIVISION

Time Table No. 155

February 2, 1936

Kerman and Visalia Branches

EASTWARD				FIRST CLASS					WESTWARD FIRST CLASS				
Capacity of Sidings in Car Lengths				348 Motor Leave Daily	58 Sequoia Leave Daily	Distance from San Francisco	STATIONS	Distance from Exeter	341 Motor Arrive Daily	347 Motor Arrive Daily	57 Sequoia Arrive Daily		
48 WYP						193.0	TO-R KERMAN 6.7	70.2					
59						199.7	MC MULLIN 5.4	63.5					
39						205.1	RAISIN CITY 5.6	58.1					
48						210.7	CARUTHERS 6.1	52.5					
39						216.8	CANDO 3.5	46.4					
						220.3	LATON & WESTERN RY. CROSSING (Stop) 2.7	42.9					
47						223.0	HARDWICK 6.1	40.2					
East 40 } WYP West 35 } Yard				2.00PM		229.1	TO-R ARMONA 3.1	34.1	s 1.50PM				
I						232.2	A. T. & S. F. CROSSING 0.3	31.0					
66 BKP Yard				s 2.10		232.5	TO-R HANFORD 1.4	30.7	1.40PM	s 3.35PM			
Spur						233.9	SHELL 3.7	29.3					
54				2.21		237.6	REMNOY 7.7	25.6					
94 WOYP Yard				s **3.08**	8.20AM	245.3	A.B.S. { TO-R GOSHEN JCT. 7.8	17.9		s **3.08**	s 8.45PM		
41 P				s 3.30	s 8.40	253.1	A.B.S. { VISALIA 0.1	10.1		s 2.20	s 8.20		
						253.2	A. T. & S. F. CROSSING Stop 2.0	10.0					
P				3.40	8.50	255.2	AMBLER 2.1	8.0		2.07	8.07		
Spur						257.3	RECTOR 1.7	5.9					
7 P				3.46	8.56	259.0	FARMERSVILLE 1.2	4.2		2.01	8.01		
P				3.48	8.58	260.2	A.B.S. { GIANT OAK 3.0	3.0		1.58	7.58		
74 KWYP				s 3.55PM	s 9.05AM	263.2	A.B.S. { TO-R EXETER	0.0		1.53PM	7.53PM		
				Arrive Daily	Arrive Daily		(70.2)		Leave Daily	Leave Daily	Leave Daily		
				(1.55) 17.79	(0.45) 23.86		........Time over District........ ....Average Speed per Hour........		(0.10) 20.40	(1.42) 18.05	(0.52) 20.65		

Time Table No. 155

February 2, 1936

Riverdale Branch

EASTWARD				WESTWARD	
Capacity of Sidings in Car Lengths		Distance from San Francisco	STATIONS	Distance from Hardwick	
Y		181.9	INGLE 5.3	42.3	
39		187.2	TRANQUILITY 4.5	37.0	
56		191.7	SAN JOAQUIN 3.3	32.5	
		194.9	CALDWELL 4.1	29.3	
25		199.0	TO HELM 7.2	25.2	
20		206.2	BURREL 3.2	18.0	
		209.4	BENDER 5.2	14.8	
7		214.6	TO RIVERDALE 2.6	9.6	
Spur 4		217.2	ROBINSON 2.0	7.0	
Spur 3		219.2	HUB 1.8	5.0	
		221.0	LATON & WESTERN RY. CROSSING (Stop) 3.2	3.2	
52 Yard		224.2	HARDWICK	0.0	
			(42.3)		
			..........Time over District.......... ....Average Speed per Hour..........		

Time Table No. 155

February 2, 1936

Coalinga Branch

EASTWARD				WESTWARD	
Capacity of Sidings in Car Lengths		Distance from San Francisco	STATIONS	Distance from Leroy	
East 40 } WYP West 35 } Yard		229.1	TO-R ARMONA 2.1	42.9	
Spur		231.2	ORION 2.7	40.8	
57 P		233.9	TO LEMOORE 1.5	38.1	
14 Spur		235.4	HEINLEN 1.1	36.6	
65 YP		236.5	ROSSI 2.9	35.5	
5 P		239.4	LETHENT 6.7	32.6	
48 P		246.1	WESTHAVEN 6.6	25.9	
39 P		252.7	TO HURON 7.3	19.3	
14 P		260.0	TURK 6.7	12.0	
38 P		266.7	ORA 1.7	5.3	
71 YP Yard		268.4	TO-R COALINGA 1.5	3.6	
16 Spur		269.9	CRUMP 2.1	2.1	
Spur		272.0	LEROY	0.0	
			(42.9)		

..........Time over District..........
..........Average Speed per Hour..........

Time Table No. 155

February 2, 1936

Oil City Branch

EASTWARD									WESTWARD				
Capacity of Sidings in Car Lengths						Distance from San Francisco	STATIONS	Distance from Oil City					
						308.6	R OIL JCT. 2.5	5.1					
						311.1	SEGURO 0.5	2.6					
						311.6	MALTHA 2.1	2.1					
						313.7	OIL CITY	0.0					
							5.1						

........Time over District........
........Average speed per hour........

Note.—Oil Jct. to Oil City operated as part of Bakersfield yard.

Capacity of Sidings in Car Lengths	EASTWARD	Distance from San Francisco		Time Table No. 155 February 2, 1936 Clovis Branch STATIONS	Distance from Friant	WESTWARD
Yard BKWOTYP		205.5	TO-R	FRESNO	24.4	
				1.6		
I		207.1		FRESNO TOWER A. T. & S. F. CROSSING	22.8	
				2.3		
Spur		209.4		BARTON	20.5	
				2.2		
Spur 18		211.6		GRANZ	18.3	
				0.2		
Spur 44		211.8		MALTERMORO	18.1	
				0.3		
		212.1		NAVIN	17.8	
				0.8		
10		212.9		LAS PALMAS	17.0	
				0.3		
		213.2		FRESNO INTERURBAN RY. CROSSING	16.7	
				0.7		
No Siding		213.9		VANRIS	16.0	
				1.0		
27		214.9		TARPEY	15.0	
				1.2		
17		216.1		MELVIN	13.8	
				1.3		
37 W		217.4	TO	CLOVIS	12.5	
				1.1		
7		218.5		GLORIETTA	11.4	
				2.4		
67		220.9		PINEDALE JCT.	9.0	
				2.0		
38		222.9		GORDON	7.0	
				0.7		
31		223.6		EL PRADO	6.3	
				2.1		
		225.7		ROCKFIELD	4.2	
				0.3		
		226.0		GAND	3.9	
				3.9		
63 WT Yard		229.9		FRIANT	0.0	
				(24.4)		

..................Time over District..................
..............Average speed per hour..............

Capacity of Sidings in Car Lengths	EASTWARD	Distance from San Francisco		Time Table No. 155 February 2, 1936 Success Branch STATIONS	Distance from Clavicle	WESTWARD
Yard 42 BKWYP		274.8	TO-R	PORTERVILLE-OLIVE ST.	13.3	
				0.8		
		275.6		A. T & S. F. CROSSING (Stop)	12.5	
				3.0		
		278.6		PERNU JCT.	9.5	
				1.4		
15		280.0		WORTH	8.1	
				2.4		
26		282.4		SUCCESS	5.7	
				5.7		
		288.1		CLAVICLE	0.0	
				(13.3)		

..................Time over District..................
..............Average speed pe ı hour..............

Capacity of Sidings in Car Lengths	EASTWARD	Distance from San Francisco		Time Table No. 155 February 2, 1936 Pernu Branch STATIONS	Distance from Pernu	WESTWARD
		278.6		PERNU JCT.	1.3	
				0.7		
Spur		279.3		TANDY	0.6	
				0.6		
Spur		279.9		PERNU	0.0	
				(1.3)		

..................Time over District..................
..............Average speed per hour..............

Capacity of Sidings in Car Lengths	EASTWARD	Distance from San Francisco		Time Table No. 155 February 2, 1936 Stratford Branch STATIONS	Distance from Stratford	WESTWARD
41 Y		244.1	TO	STRATFORD	0.0	
				4.2		
39		239.9		CUNEO	4.2	
				3.4		
65 YP		236.5		ROSSI	7.6	
				(7.6)		

..................Time over District..................
..............Average speed per hour..............

Capacity of Sidings in Car Lengths	EASTWARD	Distance from San Francisco		Time Table No. 155 February 2, 1936 Richgrove Branch STATIONS	Distance from Jovista	WESTWARD
72		294.9		RICHGROVE	4.1	
				2.7		
50		297.6		TROCHA	1.4	
				1.4		
18		299.0		JOVISTA	0.0	
				(4.1)		

..................Time over District..................
..............Average speed per hour..............

FRESNO SUBDIVISION

EASTWARD

WESTWARD

Time Table No. 155

February 2, 1936

McKittrick Branch

Capacity of Sidings in Car Lengths	Distance from San Francisco		STATIONS		Distance from Olig
KI	313.6	TO-R	KERN JCT.	1.7	49.1
P	315.3		BAKERSFIELD CORRALS	1.4	47.4
15	316.7		STRADER	2.1	46.0
43 P	318.8		WIBLE ORCHARD	1.7	43.9
	320.5		VENOLA	2.1	42.2
54 YP	322.6		GOSFORD	5.8	40.1
46	328.4		STEVENS	2.3	34.3
Spur 3	330.7		STRAND	5.4	32.0
	336.1		RIO BRAVO	9.3	26.6
	345.4		KILOWATT	0.9	17.3
91	346.3	TO	BUTTONWILLOW	4.2	16.4
64	350.5		LOKERN	10.1	12.2
30 Y	360.6		McKITTRICK	2.1	2.1
	362.7		OLIG		0.0
			(49.1)		

.................Time over District.................
..............Average speed per hour..............

TEHACHAPI SUBDIVISION

EASTWARD

WESTWARD

Time Table No. 155

February 2, 1936

Arvin Branch

Capacity of Sidings in Car Lengths	Distance from San Francisco	STATIONS		Distance from Arvin
	316.6	MAGUNDEN	0.3	16.5
	316.9	ALGOSO	4.2	16.2
	321.1	HARPERTOWN	3.5	12.0
	324.6	LAMONT	2.2	8.5
	326.8	RIBIER	2.0	6.3
	328.8	DI GIORGIO	1.9	4.3
	330.7	GIFFIN JCT.	2.4	2.4
	333.1	ARVIN		0.0
		(16.5)		

.........Times over District.........
.........Average speed per hour.........

Additional Stations { GIFFIN.....332.1 (on Spur 1.4 miles from Giffin Jct.)
VACCARO..334.4 (on spur 1.3 miles from Arvin)

MOJAVE SUBDIVISION

EASTWARD

WESTWARD

Time Table No. 155

February 2, 1936

Owenyo Branch

Capacity of Sidings in Car Lengths	FIRST CLASS 788 Mixed Leave Daily Ex. Sunday	Distance from San Francisco		STATIONS		Distance from Owenyo	SECOND CLASS 789 Mixed Arrive Daily Ex. Monday
BKWOTYP Yard	1.45AM	380.7	TO-R	MOJAVE	1.3	143.5	s 12.30AM
45	f 1.49	380.8		CHAFFEE	3.2	142.2	f 12.20
48	f 1.56	384.0		CAMBIO	8.9	139.0	f 12.05AM
48	f 2.15	392.9		NEURALIA	4.4	130.1	f 11.45PM
48	f 2.24	397.3		CINCO	5.2	125.7	f 11.30
East 48 W West 48	s 2.39	402.5		CANTIL	2.8	120.5	s 11.15
Spur 15	f	405.3		GYPSITE	2.2	117.7	f
39	f 2.50	407.5		CENEDA	1.0	115.5	f 10.50
2	f 2.52	408.5		SALTDALE	2.1	114.5	f 10.45
	f	410.6		TOBY	1.6	112.4	f
East 48 Y West 70	f 3.00	412.2		GARLOCK	4.2	110.8	f 10.35
48	f 3.09	416.4		GOLER	4.1	106.6	f 10.25
48	f 3.20	420.5		RAND	7.9	102.5	f 10.15
Y 48 Yard	s 4.05	428.4	TO-R	SEARLES	4.4	94.6	s 9.55
48	f 4.15	432.8		RADEMACHER	5.5	90.2	f 9.10
52	f 4.26	438.3		CODE	8.9	84.7	f 8.55
48	s 4.48	447.2		INYOKERN	4.5	75.8	s 8.35
49 W	f 4.58	451.7		LELITER	4.6	71.3	f 8.20
48	s 5.08	456.3		BROWN	4.4	66.7	s 8.10
48	f 5.17	460.7		LINNIE	7.6	62.3	f 7.53
47	s 5.35	468.3		LITTLE LAKE	3.2	54.7	s 7.35
48 Y	f 5.45	471.5		COSO	4.1	51.5	f 7.25
48	f 5.55	475.6		SYKES	8.5	47.4	f 7.15
47 W	f 6.17	484.1		HAIWEE	4.4	38.9	f 6.55
52	f 6.26	488.5		LOCO	4.8	34.5	f 6.45
48	f 6.36	493.3		OLANCHA	4.4	29.7	f 6.35
52	s 6.50	497.7		CARTAGO	4.6	25.3	s 6.25
52	f 7.00	502.3		MONACHEE	4.0	20.7	f 6.01
52	f 7.08	506.3		BRIER	2.9	16.7	f 5.54
	f	509.2		BARTLETT	5.1	13.8	f
52 W	f 7.24	514.3		DIAZ	4.5	8.7	f 5.40
East 56 West 52	s 8.00	518.8		LONE PINE	4.2	4.2	s 5.30
37 KOY Yard	s 8.15AM	523.0	TO-R	OWENYO		0.0	5.15PM
	Arrive Daily Ex. Sunday			(143.5)			Leave Daily Ex. Sunday
	(6.30)			Time over District			(7.15)
	22.07			Average speed per hour			19.79

RULE 2. Watch inspectors:

S. A. Pope, Manager of Time Service, 65 Market St., San Francisco.

Fresno	Bert Fuller, 1335 Fulton St.	Visalia	C. T. Kathe
Porterville	Frank Haener	Exeter	W. B. Adams
Hanford	Hanford Jewelry Co.	Bakersfield	J. N. Cheney, 801 Baker St.
Lancaster	C. E. Miller		
San Fernando	F. G. Marshall	Mojave	A. Ogulnick
Los Angeles	Newton Moore, 301 O. T. Johnson Bldg. Geo. D. Davidson Co., 445 S. Spring St. O. H. Patzer, 2708 North Broadway		

RULE 3. Conductors on eastward Santa Fe trains originating at Bakersfield will show on reverse side of Kern Jct. register ticket watch comparison made at Santa Fe station Bakersfield, also comparison with enginemen.

RULE 14 (d). As specified below, four long and one short sounds will be indication that flagman may return from west as prescribed by Rule 99.

Famoso	Trains on Exeter main track.
Ducor	Trains on Minkler-Southern Branch.
Exeter	Trains on Visalia Branch.
Hardwick	Trains on Riverdale Branch.
Ingle	Trains on Riverdale Branch.
Goshen Jct	Trains on Kerman Branch.

RULE 14 (e). As specified below, six long sounds will be indication that flagman may return from east as prescribed by Rule 99.

Fresno	Trains on Exeter main track and Clovis Branch.
Porterville	Trains on Success Branch.
Rossi	Trains on Stratford Branch.
Goshen Junction	Trains on Visalia Branch.
Ingle	Trains on Riverdale Branch.
Richgrove	Trains on Richgrove Branch.
Magunden	Trains on Arvin Branch.
Mojave	Trains on Owenyo Branch.

RULES 17 and 19. Night signals will be displayed through all tunnels.

RULE 21. In Bakersfield yard indicators on engines will be displayed to relief track.

RULE D-71. Trains and engines may move between Calwa Tower and Clinton Ave., Fresno, with current of traffic irrespective of time table superiority but must avoid delaying first class trains.

RULE S-72. Westward trains are superior to trains of the same class in the opposite direction.

RULE 83. Train registers are not maintained at Calwa Tower or Bena. When an observation check be made between Fresno and Calwa Tower, and between Bakersfield and Bena, it will apply at end of double track.

Trains approaching each other between these stations will reduce speed sufficiently to permit identification.

When first class trains on opposite track between Mojave and Tehachapi are identified, it will not be necessary to obtain check of such trains before making movements in the same direction between Summit Switch and Mojave.

Rule 14-K must be applied when approaching trains on opposite track.

RULE 83 (A). At the following stations, only the trains indicated will register.

Oil Jct. Lancaster	Trains originating and terminating.
Famoso	Trains to and from Exeter main track.
Tehachapi	First and second class trains, and trains originating and terminating.
Goshen Jct	No. 55, No. 56, No. 57, No. 58 and trains to and from Visalia and Kerman Branches, and extras originating and terminating.

Extra trains register at Porterville Olive St., Exeter, Armona and Coalinga.

RULE 83 (B). At open train order offices trains may register by ticket as follows:

Kern Jct	Santa Fe trains, S. P. first class trains and Westward light engines.
Tehachapi	First and second class trains.
Porterville Olive St.	First class trains.
Famoso	Trains to and from Exeter Main Track.

Operator Kern Jct. will report arrival and departure Santa Fe first-class trains to Operator Bakersfield, who will enter same on register.

Operator Kern Jct. will report arrival and departure of all scheduled trains to operator Santa Fe station Bakersfield, who will enter same on Southern Pacific register located at Santa Fe station Bakersfield.

RULE 83 (D). Westward Santa Fe trains via Southern Pacific will get clearance and train orders from operator Santa Fe station Bakersfield authorizing movement from Oil Junction westward.

Eastward Clovis Branch trains destined to Fresno Interurban secure train orders or clearance from operator at Fresno Tower, authorizing movement over Fresno Interurban.

Conductors and Engineers from Riverdale Branch to Western Division, in addition to orders and clearance signed by Chief Dispatcher of Western Division, authorizing movement from Ingle to Kerman on Los Banos subdivision of Western Division, will also procure from operator at the same point where such orders and clearances are issued, clearance signed by Chief Dispatcher of the San Joaquin Division.

Trains via Visalia and Kerman branches must obtain clearance before leaving Goshen Jct. when operator on duty.

RULE 83 (E). A train, when authorized by train order, may check the register against an extra train and proceed if such extra train appears on the register with the number and date of its restricting order registered in column captioned "Signals".

When a train is so authorized to check the register, it must register and place the restricting order number and date in column captioned "Signals".

RULE 93. Yard limits are established at:

Fresno
Goshen Jct.
Coalinga
Armona
Hanford
Sanger
Reedley
Delano
Tulare
Bakersfield
Visalia
Exeter
Lindsay
Porterville Olive St.
Dinuba
Kingsburg
Friant
Tehachapi
Summit Switch
Eric
Mojave
Searles
Owenyo
Saugus
Selma
Lancaster
Vincent

Fresno: Limits are defined by yard limit signs at the following points:

Kerman Line	Mile Post 206.32.
Merced Line	Mile Post 199.08.
Bakersfield Line	Mile Post 210.81.
Exeter Main Track	Mile Post 208.15.
Clovis Branch	Mile Post 209.6.

Trains or engines will not move against current of traffic on double track between Divisadero Street and Clinton Avenue and between Cherry Avenue and Calwa Tower, Fresno, except on authority of Yardmaster. When making movements against current of traffic, trains or engines must be preceded by flagman over railway and street crossings at grade where wigwags are installed, protecting these crossings during movements.

Trains arriving and departing via Los Banos line at Fresno will receive proceed signal from herder at Divisadero Street, green flag by day and green light by night.

Westward trains or engines must receive proceed signal from yardman at Kern Street; and eastward trains or engines must receive proceed signal from yardman at Merced Street.

Trains may use No. 1 running track between Clinton Ave. and Biola Jct.

Mojave: First class trains may pass through Mojave without hand signals, providing switches are properly lined for such movement, and will move with caution irrespective of timetable superiority between Signals 3802 and 3811. Inferior trains entering or leaving Mojave must receive green signal unless yardmaster or his subordinate notifies train that they may enter or leave without green signal.

Trains leaving east end of yard may proceed without signal from herder provided they are notified switches are properly lined.

Trains from Owenyo Branch stop before fouling main track or blocking highway crossing regardless of position of derailer or signals received.

Unless yardmaster or his subordinate instruct otherwise, crossover movement from Owenyo Branch to Mojave will be made as follows: First throw derailer on Owenyo Branch, second throw trailing point switch on eastward main track, third crossover switch on westward main track, fourth Owenyo Branch switch—then wait five minutes before proceeding. Be governed by Rule 93.

Following code of signals will govern eastward trains entering yard:

Southern Pacific:

Passenger trains	One long.
Freight trains	One short, one long, one short.

Santa Fe:

Passenger trains	One long, one short.
Freight trains	One long, one short, one long.

RULE D-97 (A). Will apply between Tehachapi and Summit Switch.

RULE 98. RAILROAD CROSSINGS AT GRADE NOT INTERLOCKED

A. T. & S. F. Railway, 744 feet east of Lacjac, STOP.

A. T. & S. F. Railway, 14718 feet west of Taurusa, STOP.

A. T. & S. F. Railway, 602 feet east of Visalia, STOP, and not pass over crossing without receiving proceed signal from flagman, who must precede train.

Laton & Western Railway, 2.7 miles west of Hardwick, STOP.

Laton & Western Railway, 1.8 miles east of Hub, STOP.

A. T. & S. F. Railway (on Success Branch), 4515 feet east of Porterville, STOP.

Fresno Interurban Railway, 1771 feet east of Las Palmas.

Fresno—Trains from Clovis Branch and Exeter main track stop at "stop" board at junction of these lines.

Goshen Jct.—Trains from Visalia Branch stop at "stop" board east end of yard.

End of the Visalia Branch will be at first switch east of the station where it enters Bakersfield-Fresno main track.

RULE 103 (A). At Selma no switching movements will be made over West Front Street while switching industrial tracks east of station and opposite Libby, McNeill and Libby Plant unless crossing is protected by member of crew.

No train, engine, car or motor shall be stored within 100 feet of either property line of County Road Crossing or Western Dairy Products track at Tipton, unless crossing is protected by flagman.

At Armona no switching movements will be made over Lake Street crossing unless protected by member ot crew, or crossing flagman is on duty protecting crossing.

Trains switching Knudsen Laboratories, Inc. (Creamery) Spur, Visalia, must stop before making reverse movement across Goshen Avenue crossing.

RULE 104. The normal position of switches at junctions will be for main tracks.

Exceptions:

Fresno Yard, Clinton Avenue (end of double track) for eastward track. This is an oil buffer spring switch.

Fresno, junction Los Banos line, for eastward track. This is an oil buffer spring switch.

Bena (end of double track) for westward track. This is an oil buffer spring switch.

Tehachapi (end of double track) for eastward track. This is an oil buffer spring switch.

Mojave (end of double track) for westward track.

Hardwick	for Kerman Branch
Armona	for Coalinga Branch
Rossi	for Coalinga Branch
Pernu Jct.	for Success Branch
Gosford	for McKittrick Branch

Derailers in main track.
McKittrick. East wye switch is spring switch and serves as derail.
Porterville. 310 feet east of junction switch on Success Branch.
Mojave. 230 feet east of junction switch on Owenyo Branch.
Famoso. 168 feet west of junction switch, on Exeter main track.

RULE 105. Track next to and north of main track at Ducor will be used as siding No. 1. Second track north of main track, will be used as Minkler Southern Ry. main or No. 2 track. Trains will use extreme east switch to enter or leave Southern Pacific main track. Inside switches will be left lined for Siding No. 2.

At Caliente, Bealville and Marcel the siding next to main track will be used as eastward siding, adjoining track will be used as westward siding. Inside siding switches are oil spring switches and normal position is for train entering siding. Trains entering siding passing an inoperative signal must assure themselves this switch is properly lined.

At Rowen the siding east of the crossovers will be used as the westward siding, the one west of the crossovers as the eastward siding.

Trains using other than the designated siding, unless authorized by the dispatcher, must be preceded by a flagman.

Track (No. 1) next to main track west of station at Tehachapi will be used as westward siding.

At Vincent siding next to main track will be used as eastward siding, adjoining track will be used as westward siding.

RULE 221. Light will not be displayed in train order signals on McKittrick, Clovis, Coalinga, Kerman, Richgrove, Riverdale, Success, Stratford and Visalia branches, except when train orders are to be delivered.

Trains will not be required to obtain clearance at Kern Jct. and Bakersfield except when such trains originate or receive orders at these stations.

RULE 221 (A). It is unnecessary for dispatchers to O. K. a clearance and operators to transmit the address and order numbers from clearance to the train dispatcher, unless requested to do so by train dispatcher, nor will they complete that portion of clearance (Form CS-2643) reading: "OK at........M........Chief Train Dispatcher," all provided that said orders affect movement of a train wholly within block system or signal dispatching limits.

If the orders affect movement, either wholly or in part, outside of the block system or signal dispatching limits, operators must repeat address and order numbers and obtain dispatcher's OK before the orders are delivered.

RULE 825. Outfit cars must not be left in front of warehouses, storehouses, lumber yards, or other buildings.

House track at Woodford must not be used for setting out or storing of cars.

RULE 834. Open-top cars loaded with rails, pipe, structural steel, poles, lumber or mounted wheels, when such lading projects above side and end walls of car, must not be placed in train next to cab of mallet engines.

RULE 869. Trainmen will ride on top of trains through yards, entering and leaving terminals, through interlocking plants, also Vincent to Saugus, Vincent to Palmdale, Summit Switch to Mojave, Summit Switch to Ilmon, Searles to Cantil, McKittrick to Lokern and at other places as instructed by conductor.

AUTOMATIC BLOCK SYSTEM

A train or engine, when backing out of a siding or other track in block system limits, will, unless backed to clear block signal, proceed as if signal be in stop position.

That section of track in Fresno between Tuolumne Street and Ventura Avenue is not protected by block signals. Be governed by third paragraph Rule 93.

Dwarf light signals governing movements to main track located as follows: Signals 2020 and 2022 Clinton Ave., Fresno, Signals 2565 and 2625 at Exeter, Signal 2870 Ducor, Signal 3627 Summit Switch, and Signal 3679 Eric. The first switch or derail lined, dwarf signal will indicate red. When all switches and derail are lined dwarf signal will indicate proceed. If signal indicates stop after proper line up has been made, a train will not move to main track except as provided by Rules 509 and 99.

Fresno.—West switch and derail of running track, Fresno Yard near Biola Jct., the Biola main track junction switch and derail, and switch No. 2 track west of Ashland Ave. are hand operated by using the switch levers on side of electric switch machines.

Signals governing movements from Biola Branch and from the west end of No. 1 track will indicate stop until derails and switches have been properly lined for route desired, when signals will indicate proceed.

Exeter.—Signal 2628 at junction Visalia Branch and Exeter main track normally indicates stop until crossover lined for movement to main track.

Bena.—Eastward trains leaving siding will be governed by dwarf light Signal 3282 which will indicate proceed after siding switch has been thrown to reverse position for two minutes.

Cable-Tehachapi.—Signals 3582 and 3585 have included in their control limits a special protective device. When these signals indicate stop, careful inspection must be made of and at the fourteen foot arch 358.57 known as the 7th Tehachapi creek crossing, and it must be known that arch and embankment are safe for passage of trains before proceeding.

Tehachapi.—Trains on No. 1 track at Tehachapi ready to leave, finding dwarf light Signal 3595 at stop, will push button located in box on post two feet east of Signal 3593. After pushing this button signal will clear in two minutes if no trains in block.

Warren.—When dwarf light signals located at either end of siding indicate stop, trains entering will be preceded by a flagman.

Searles.—Automatic block signals 4277 and 4268, located at east and west end of Tunnel 29 at Searles.

Knife switches have been installed in relay boxes located at these signals for use of operators of motor cars passing through tunnel.

Motor cars should stop and if signal indicates proceed, switch in box should be thrown to reverse position which will place signals at stop before entering tunnel. After passing through tunnel, stop must be made at signal and knife switch thrown to reverse position, which will clear signals.

OIL BUFFER SPRING SWITCHES

When a block signal in advance of a facing point oil buffer spring switch indicates "STOP", careful examination of switch must be made before passing over it.

When making trailing point movement and train is stopped on switches, a reverse movement must not be made, nor the slack taken until the switch has been thrown by hand. When movement has been completed through switch, reverse movement must not be made until point closes.

Running switches are prohibited and sand, blow-off cocks, and injectors must not be used nor boosters started while passing over these switches.

Oil buffer spring switches are located as follows, and speed indicated must not be exceeded when passing over such switches.

		M.P.H.
Fresno, Clinton Ave., end double track	Trailing westward	30
	Facing eastward	20
Fresno, junction Los Banos line	Trailing eastward	20
	Facing westward	10
Bena, end double track	Trailing eastward	30
	Facing westward	20
Bena, west end siding	Trailing westward	50
Ilmon, west end	Trailing westward	30
	Facing eastward	30
Caliente, west end siding No. 2	Trailing westward	10
	Facing eastward	10
Caliente, east end siding No. 1	Trailing eastward	10
	Facing westward	10
Allard, west end	Trailing westward	30
	Facing eastward	30
Bealville, west end siding No. 2	Trailing westward	10
	Facing eastward	10
Bealville, east end siding No. 1	Trailing eastward	10
	Facing westward	10
Rowen, west end	Trailing westward	30
	Facing eastward	30
Walong, west end	Trailing westward	30
	Facing eastward	30
Marcel, west end siding No. 2	Trailing westward	10
	Facing eastward	10
Marcel, east end siding No. 1	Trailing eastward	10
	Facing westward	10
Cable, west end	Trailing westward	30
	Facing eastward	30
Tehachapi, west end	Trailing westward	30
	Facing eastward	30
Summit Switch, east end	Trailing eastward	30

INTERLOCKING

At all interlocking plants, when route lined is not to be used, following signal will be sounded by Engineers, one short, two long and one short (o— —o).

FRESNO TOWER—A. T. & S. F. Crossing 1.6 miles east of Fresno on Clovis Branch

For main track, one long whistle (———).

To or from spur track, one short and two long whistles (o — —).

SUN MAID TOWER—A. T. & S. F. Crossing 1.5 miles east of Fresno on Exeter main track

One long whistle (———).

CALWA TOWER—A. T. & S. F. Crossing and double track 0.8 miles east of Calwa

Eastward trains approaching end of double track will call for switch and derailer by one long, one short and one long whistle (——— o ———).

Westward trains, one long whistle for crossing and for double track (———).

HANFORD TOWER—A. T. & S. F. Crossing 0.3 miles west of Hanford

One long whistle (———).

TULARE TOWER—A. T. & S. F. Crossing 0.3 miles west of Tulare

One long whistle (———).

KERN JCT. TOWER—A. T. & S. F Crossing, double track and McKittrick Branch 0.7 mile east of Bakersfield

For main track, one long whistle (———).

For movement over crossing on siding, one long, one short and one long whistle (——— o ———).

From S. P. to A. T. S. F. main track, one short and two long whistles (o ——— ———).

Between main track and transfer track, one short, one long and one short whistle (o ——— o).

No. 1 track, two short, one long and one short whistles (o o———o).

Dwarf light signals opposite end of double track governing westward movement are as follows:

Green............Westward track to S. P. single track.
Yellow...........To Santa Fe westward double track or S. P. No. 1 track.

Dwarf light signal for eastward movement is located at west limits of interlocking plant. Light signals as follows:

Green............Eastward main track.
Yellow...........Against current of traffic.

Transfer tracks have pipe connected derails to main track (transfer switch).

At Kern Jct. only, Rule 628 is modified to permit movement, without stopping, of helper cuts only, past interlocking signals in stop position, provided yellow signal is received from the towerman in tower or on ground, and helper engineer sees that track is properly lined for movement to be made.

TEHACHAPI

Main track movements (to or from double track) one long whistle (———).

No. 1 siding, one short, one long and one short whistle (o ——— o).

CALIENTE, ALLARD, BEALVILLE, CLIFF, WOODFORD, MARCEL

The east and west switches of sidings at Caliente, Bealville, Cliff, Woodford, Marcel and the east switch of siding at Allard are interlocked and controlled from Telegraph office. All other switches are hand throw. The switches and signals at Allard and Cliff are controlled by the plant at Bealville.

Interlocking limits extend on main track from the eastward signal, located fifty (50) feet west of the west switch, to the westward signal, located fifty (50) feet east of the east switch at Caliente, Woodford and Marcel, and on both main track and siding at Woodford, and at Bealville from the eastward signal, located fifty (50) feet west of the west switch Allard to westward signal, located fifty (50) feet east of the east switch Cliff. All signals within these limits are interlocking, except Signals 3412 and 3417, which are automatic.

When the eastbound interlocking signals east end Bealville or the westbound interlocking signals west end Cliff are inoperative, trains must be preceded by flagman to the next signal.

Trains stopped by signals must communicate with signal operator by telephone located in telephone booths at east and west switches and be governed by his instructions. Additional telephones are provided at derail west end house track Woodford, and at derail of house track extension at Caliente. If instructed by signal operator to throw interlocked switch by hand, follow instructions posted in telephone booth.

The member of crew cranking switch over, after receiving permission from signal operator, must notify rear member of his crew in order that switch will be returned to normal position, or remain at switch and return it to normal position, unless instructed by signal operator to leave switch open.

When for any reason, proceed indication of an interlocking signal cannot be acted upon at once signal operator must immediately be notified.

Trains or engines entering main track, except where fixed signals govern movement, must receive authority from signal operator then may proceed with caution, not exceeding twelve (12) miles per hour to next signal.

At Cliff, Spur switch west end siding will be hand operated and trains must not enter or leave spur except on telephone authority from signal operator at Bealville.

At Woodford "Take Siding Indicator" mounted on mast of westward interlocking signal will govern westward trains that are to use house track.

When westward third class and extra trains are given main track at Allard, and are unable to proceed further ahead of superior trains in the same direction, they will immediately advise the signal operator at Bealville.

Trains entering sidings at Caliente, Bealville and Marcel will stop clear of adjacent siding unless a proceed signal is indicated in light signal govering the movement to main track.

FRESNO, OLIVE AVE. CROSSING, AUTOMATIC INTERLOCKER

Interlocking limits extend from eastward Light Type Signal SA-2032, located 750 feet west of Fresno Traction Company crossing to westward Light Type Signal SA-2032 located 750 feet east of this crossing.

When these signals display stop, trains will be governed by interlocking rules within the interlocking limits and Rule 509 within the automatic portion of the block beyond the interlocking limits and will be preceded to crossing by flagman.

Dwarf light type signals installed between main tracks and located 80 feet east and west of this crossing govern moving against current of traffic. These signals indicate stop only and trains must be preceded by flagman who will give proceed signal from center of crossing.

TRAIN AND AIR INSPECTION

At the following stations freight trains descending grade between Caliente and Lang will stop 10 minutes to allow heat to equalize in wheels and make inspection:

Ravenna.

Marcel Rowen.—Or in making other stops, inspection may be made provided initial run is not to exceed 8 miles, succeeding runs not to exceed 10 miles.

A continuous run of 10 miles will not be made where the run from the last inspection point was less than 7 miles.

Warren.

Owenyo Branch.—Rand. If retainers are not used, need not stop if in opinion of conductor it is safe to do so.

Freight trains must not run more than 40 miles without a stop for inspection: Except run may be made by westward freight trains, Saugus to Lancaster, Ravenna to Mojave, also from Bakersfield to Tipton and Tipton to Fresno or vice versa without stopping for train inspection when in the judgment of the conductor it is safe to do so. Inspection will be made at any intermediate stops.

AIR BRAKE RULE 11.

Air brake inspection at points where no car inspectors are on duty, and motive power and/or engine crew or train crew is changed on a freight train, shall be made as follows:

After the train is made up and the engine attached, the engineer will apply the brakes with a 20 pound service reduction and leave them applied. The trainmen will then pass along the train to determine that the brake is applied on each car. The numbers of any cars found with inoperative air brakes must be reported on Form 2809 and such cars assembled and switched to the rear of the train, next ahead of the caboose, before leaving that station. After this inspection has been made, brakes have been released, and trainmen have noted that normal brake pipe pressure has been restored as indicated on caboose gauge, and have given signal to engineer, the latter must comply with last part of Rule 11 to avoid brakes sticking from an overcharge of the brake system, etc.

If it is necessary to switch any cars to the rear account brakes being inoperative, Rule 17 must be complied with before departure.

Rule 34 must be observed to determine by rolling inspection that each brake releases properly.

Attention is directed to the Safety Appliance Act which requires that whenever any train is operated with power or train brakes, not less than 85 per cent. of the cars of such train shall have their brakes used and operated by the engineer of the locomotive drawing such train; and all power-brake cars in every such train which are associated together with the 85 per cent., shall have their brakes so used and operated.

AIR BRAKE RULE 16.

Passenger Trains: Make running air brake test at Summit Switch and between initial and crossover switch at Vincent. Not necessary to make running test on passenger trains leaving Mojave that have not had the continuity of the brake pipe broken. Eastward Santa Fe passenger trains leaving Kern Jct. will not make running test. Within yard limits of Fresno, running air brake test will be made only when leaving Fresno.

When running test is made leaving Fresno eastward and Bakersfield eastward and westward, trainmen will use Signal 16-H instead of hand or lamp signal.

On westward passenger trains leaving Bakersfield, running test shall not be made until rear car has cleared Baker Street.

Freight Trains: Freight trains not stopping at Summit Switch will make running air brake test between wye switches as follows: While working steam, engineer will make a reduction of approximately 7 pounds, waiting for slack to adjust itself and then add about 3 pounds, making total reduction of 10 pounds before releasing.

Conductor will note reduction on caboose gauge and following build up in pressure when brakes are released, then give proceed signal which will be relayed by other trainmen from their portion of the train, providing they note retainers releasing in their vicinity.

If conductor is on the head end, the rear brakeman is held responsible for such observance of the gauge as will insure against danger from closed angle cock or low pressure.

When such observance indicates danger, take every needed precaution as the circumstances warrant.

If releasing of brakes cannot be made at a greater speed than 15 miles per hour, stop and make rear end test.

Whenever plug tests or running tests, whichever are required under the rules, have been made on eastward trains at Tehachapi, it will not be necessary to make running tests on such trains not stopping at Summit Switch.

Westward freight trains that do not have helpers to cut out at Vincent and do not stop there for other operating reasons, will turn up the retaining valves on the first ten cars behind the engine at the east distant signal approaching Vincent, and will make air brake running test between passing track switches as follows:

While working steam and not allowing driver brakes to apply, follow the same procedure as outlined in instructions relative to making the freight train running test at Summit Switch, with the exception that a release may be made at a speed not slower than 8 miles per hour. If train has to stop for any reason, or if speed of at least 8 miles per hour cannot be made at time release is desired, standing air brake test as per Rule 17 of the air brake rules will be made.

On Eastward freight trains not having helpers to cut out or required to stop at Vincent for operating reasons, they will follow the same procedure as outlined in next paragraph above, except that one retaining valve for each 115 M's contained in train will be used. These retaining valves must be turned up at or near west distant signal, the retaining valves on head portion of train to be turned up first.

AIR BRAKE RULE 17.

Rear end test will be made in accordance with Rules 17 and 17-A of the Air Brake Rules, and this test will also be made at the following places under the conditions hereinafter stated:

Vincent	Freight trains stopping.
Summit Switch	All trains stopping.
Mojave	Freight trains not originating.

Leading engineer will not signal for rear end test on trains having helpers until such helpers indicate by one blast of the whistle that the train is ready for the test.

AIR BRAKE RULE 56.

Retainers will be used on passenger trains as follows:

Westward trains......Tehachapi to Caliente—All retainers

Retainers on all head end cars of eastward passenger trains (except Train No. 56) will be turned up at Summit Switch, remainder of retainers to be turned up at Cameron without stopping, all retainers being used to Mojave. When retainers are thus used speed of trains must not exceed 45 miles per hour.

Retainers on all head end cars on Train No. 56 will be turned up at Tehachapi, remainder of retainers to be turned up at Cameron without stopping, all retainers being used to Mojave. When retainers are thus used speed of train must not exceed 45 miles per hour.

Unless otherwise provided, trains having not to exceed two head end cars available retainers will be used Cameron to Mojave and Tehachapi to Tunnel 1.

Retainers will be used on freight trains as follows:

Eastward trains	Cameron to Mojave.
Eastward trains	Vincent to Lang.
Westward trains	Vincent to Harold.
Westward trains	Tehachapi to Tunnel One.
Westward trains	McKittrick to Lokern.

Eastward Southern Pacific freight trains stopping at Summit Switch will turn up retainers there, and if train brakes are applied a speed of 20 miles per hour must not be exceeded Summit Switch to one mile east of Cameron.

On freight trains descending grade Tehachapi to Tunnel 1, Cameron to Mojave and Vincent to Lang, one pressure retaining valve must be used for each 115 M's in train. These retaining valves to be used solid on head end of train.

Descending grade between Vincent and Harold, use ten retaining valves on head end of train.

Retainers will be used on other districts when in judgment of enginemen it is deemed necessary.

Speed of freight trains will be reduced at points where trainmen are required to handle retainers.

Where retainers are used the rate of speed of freight trains on any grade of over one per cent will not exceed 25 miles per hour, and on grades of this character more than five miles long, for the first five miles the time consumed in traveling one mile shall not be less than three minutes. The above maximum speed restriction will not affect the speed on heavier grades and other locations, where the maximum is now provided. Retainers on eastward freight trains entering Mojave must not be turned down until train comes to rest on designated tracks.

Freight trains taking siding where it is necessary for them to open their own switch, and where necessary to apply train (automatic) brakes, stop and allow sufficient time to insure release of all brakes.

Conductor report to Superintendent, by wire, any failure to properly control train by air brakes and deliver to Car Inspector at first terminal list showing tonnage of each car in train. Car Inspector will add to list the piston travel of each car in train, as shown by test made before road engine is cut off, also result of three-minute test of all retainers. The list will then be forwarded to Superintendent by first mail.

The maximum tonnage per operative brake between Caliente and Mojave is 115 Ms and between Mojave and Saugus 120 Ms.

MISCELLANEOUS

1. Freight trains with twenty or more cars will detach engine when taking water except at the following stations:

All points on the Valley district		Lancaster	Eastward trains
Caliente	Eastward trains	Ravenna	Westward trains
Woodford	Eastward trains	Lang	Westward trains

In freight service with over 30 cars where it is necessary to make a short move to reach water or oil column, including that required to spot second engine of double header, locomotive must be cut off before spotting at column.

Water supply at Bealville, Marcel and Cameron is for emergency use only. Tank spouts are locked.

Take as little water as possible at Cantil and take water at Palmdale, Lang and Haiwee only when absolutely necessary.

In taking water on freight trains with helper cut in, train will be cut ahead of first helper from head end and will back to point where it is to take water. After stopping, train will be cut ahead of following helper.

4. Helpers will cut out at Vincent unless otherwise instructed. At Vincent, helpers on eastward freight trains are to be cut out at the west leg of wye or west end of siding.

Helper engines cutting out of eastward trains at Summit Switch, enter wye from east leg.

Should a stop be made short of a turnout at a point where helpers are to be cut out, cut will be made ahead of leading helper and train engine will pull head portion to clear, to prevent damage done by helper in shoving during short move.

In movement of light engines between Bakersfield and Mojave the number of engines coupled is restricted to four, except not more than two engines coupled will pass over bridges between Caliente and Ilmon.

Helpers must be placed ahead of rear end cars.

4a. For purpose of pushing trains out of yards—No locomotive will be placed behind a wooden underframe caboose or other wooden frame equipment.

Locomotives of 4000 or 4100 class will not be placed behind steel underframe cabooses.

Air will not be coupled through the pusher engine.

Yard engines regularly so used will be equipped with Russell-Jordan device to hold the coupler pin from dropping, thus making it unnecessary for employes to uncouple the pusher engine when cutting off.

In no case shall the knuckle be removed, or closed, or cutting lever temporarily fastened in release position on a pusher engine, as means of preventing coupling being made.

It will not be necessary to stop trains to detach pusher engines.

In helper Service—No helper engine will be placed behind wooden underframe cars or cabooses.

Helper engines of 4000 or 4100 class will not be placed behind steel underframe cabooses.

In no case will more than one helper engine be placed behind steel underframe cabooses.

5. Engines will not be left on No. 1 track at Tehachapi while crews are eating. When engines are left with no one attending, the reverse lever will be left on center, cylinder cocks will be left open, independent brake valve or straight air valve will be left in service position, noting amount of brake cylinder pressure before leaving the engine. No member of crew will leave their engine before engine has come to rest, and when engine or engines are left alone, tank brakes should also be set in addition to independent brakes.

This will apply at other points where similar conditions exist.

7 Engines heavier than large Moguls will not be permitted east of east switch Crump. Flanges of other engines proceeding farther must be thoroughly oiled before moving around curves.

Engines larger than Moguls will not be run between Hardwick and Riverdale. Engines larger than Moguls will not use spur at Maltermoro.

8. When engine is to be changed or cars set out or picked up, on passenger trains rear brakeman will open steam valve on rear of train and engineman will shut off the steam at yard limit boards Fresno, Bakersfield and Mojave, and station one mile boards at other points.

10. Tracks at following stations must not be used by engines larger than consolidation type. Spurs at Bena, Caliente, Gypsite, Toby, Garlock Wye and sidings at Toby, Goler and Rand.

When switching the west end of Saltdale, with 2-10-2 engines, use sufficient number of cars to prevent engine from going beyond frog.

Switching movement from spurs on heavy grades should be accomplished in a manner to make it impossible for cars to run out on main track. This can be done by stopping train between switches and by switching from spur track to train, leaving switch lined for spur track until work is completed. Do not switch cars into a siding on grade where such siding is unprotected by derail. Do not handle cars ahead of engine descending grades when practicable to avoid same. Whenever possible, when switching on heavy grades, engine should be kept on down hill side of cars being handled, or such switching moves be made against a derailer.

When switching No. 1 track at Kingsburg Winery with engines larger than 2300 class, use a sufficient number of cars to prevent engines going beyond the frogs.

20. Handling of freight cars in trains behind passenger cars carrying passengers prohibited. The term "freight car" does not include a baggage, express or mail car, or a caboose.

Baggage, express, mail, refrigerator or other head end cars must not be handled on rear of passenger trains unless trainmen can pass through them.

Club cars handled in head end of main line passenger trains must be of all steel construction.

23. Following will govern the handling of switches for the center sidings at Warren and Monolith:

Westward Trains—Heading in.

Switches will be handled in following sequence:

1. Westward main track switch.
2. Center siding switch.
3. Derailing switch.

After Train is in siding.

1. Westward main track switch.
2. Derailing switch.
3. Center siding switch.

Eastward Trains.

Switches will be handled in normal manner.

27. In addition to one engineer, one firemen, and one conductor, each steam freight, mixed or work train must have two or more brakemen, as noted below, if more than four trains are operated each way per day:

Grade	No. Cars in Train	No. Brakemen
1% or under	49 or less	2
“	50 to 75 inclusive	3
“	76 to 100 “	4
“	101 to 125 “	5
1% to 1½%	49 or less	2
“	50 to 62 “	3
“	63 to 87 “	4
“	88 to 112 “	5
“	113 to 125 “	6
Over 1½%	49 or less	2
“	50 to 57 inclusive	3
“	58 to 72 “	4
“	73 to 87 “	5
“	88 to 102 “	6
“	103 to 117 “	7
“	118 to 125 “	8

The following are grade maximums on the San Joaquin division:

1% or under	1% to 1½%	Over 1½%
Fresno-Bakersfield	Bakersfield-Ilmon	Ilmon-Tehachapi
Clovis Branch	Tehachapi-Eric	Eric-Mojave
Riverdale Branch	Mojave-Rosamond	Palmdale-Saugus
Coalinga Branch	Success Branch	Owenyo Branch
Visalia Branch		McKittrick Branch
Stratford Branch		
Kerman Branch		
Richgrove Branch		
Arvin Branch		
Rosamond-Palmdale		

28. Train movements on Richgrove Branch will not be authorized by train orders. Trains using this Branch will do so under flag protection.

Flagman will be left at Richgrove with written instructions on Form CS 2511 regulating the movement of other trains desiring to use this track.

SPEED RESTRICTIONS

Maximum speed of any passenger train must not exceed 50 miles an hour except as otherwise provided for:
Maximum speed of any freight or mixed train must not exceed 35 miles an hour except as otherwise provided for:

Speed Restrictions in Miles Per Hour, Will Apply as Follows:

Page No.	TERRITORY	PASSENGER Maximum	PASSENGER With E T-26, 32, 37, 40 P A Motors	PASSENGER With M T 1, 2, 8, 9, 23, 28, 31, 36, 57, 58 MK 5, 6, 7, 8, 9	PASSENGER With Mt. GS Sta. Fe Mt. type	PASSENGER With C 2 to 10 incl C 18 to 29 incl. F AC 4, 5, 6, MM, AM SP	FREIGHT Freight and Mixed Maximum	Engines Backing With or Without Cars	Switch Engines S-SE Type	LIGHT ENGINES RUNNING FORWARD E T 26, 32, 37, 40 P A Mt. 1, 2, 3, 4, 5 Santa Fe Mt. type	LIGHT ENGINES RUNNING FORWARD M T 1, 2, 8, 9, 23, 28, 31, 36, 57, 58 C 2 to 10 incl. C 18 to 29 incl. MK 5, 6, 7, 8, 9	LIGHT ENGINES RUNNING FORWARD F SP GS Santa Fe 3800 type	LIGHT ENGINES RUNNING FORWARD C 12, 15, 17 TW MK 2, 4, 10 AC MM AM
2	Biola Jct.-Goshen Jct., except	50	50	50	50	45	40	30	20	40	35	35	30
2	F. T. Co., Crossing, Olive Ave., Fresno	20	20	20	20	20	20	20	20	20	20	20	20
2, 3, 7	Within City Limits, Fresno, along or on across street crossings	20	20	20	20	20	20	12	12	12	12	12	12
2	Goshen Jct.-Mile Post 310, except	60	60	50	50	40	40	30	20	40	35	35	30
2	A. T. & S. F. Ry., crossing at Tulare Tower	40	40	40	40	40	35	30	20	35	35	35	30
2, 4	Mile Post 310-Mile Post 314.4	35	35	35	35	35	20	20	20	20	20	20	20
3	Fresno—Famoso, except	45	45	45			30	30	20	30	30	30	30
3	On curves at Mile Post 218.54 and 218.74	35	35	35				20	20	20	20	20	20
3	On curve west of Orris	35	35	35				20	20	20	20	20	20
4	Mile Post 314.4 - Mile Post 330	50	50	50	45	45	40	30	20	40	35	35	30
4	Mile Post 330 - Mile Post 359.2, except	30	30	28	28	28	20	15	20	25	25	20	20
4	Mile Post 333 - Mile Post 334	20	20	20	20	20	20	20	20	20	20	20	20
4	Mile Post 359.2 - One Mile east of Cameron	50	50	50	50	45	35	30	20	35	35	35	30
4	One mile east of Cameron—Mojave, except	45	45	45	45	45	20	20	20	25	25	25	25
	Westward freight trains Mojave to one mile east of Cameron						35						
4, 5	Mojave Yard, between Standard Oil switch and extreme east switch	15	15	15	15	15	10	10	15	15	15	15	15
5	Mojave-Mile Post 417, except	50	50	50	50	45	35	30	20	35	35	35	30
5	Westward freight trains M. P. 417 to Palmdale						22						
5	Mile Post 417-Lang	30	30	28	28	28	20	15	15	25	25	20	20
5	Lang-Saugus	30	30	28	28	28	22	15	15	25	25	22	22
6	Armona-Crump, except	25					25	25	20	25	25		
6	Over trestle at M.P. 267.3	15					15	15	15	15	15		
6	Crump-End ot track	8					8	8	8	8	8		
6	Kerman-Goshen Jct	30					30	30	20	30	30		
6	Goshen Jct.-Exeter, except	40					30	30	20	30	30		
6	On curve at Goshen Jct. and curve at Ambler	30					20	20	20	20	20		
6	Ingle-One mile west of Riverdale	25					25	25	20	25	25		
6	One Mile west of Riverdale-Kings River Bridge	15					15	15	15	15	15		
6	Kings River Bridge-Hardwick	25					25	25	20	25	25		
7	Fresno-Gordon, except	25					25	25	20	25	25		
7	On curves at Barton and Maltermoro	18					18	15	15	18	18		
7	Over Fresno Interurban tracks, Las Palmas	15					15	15	15	15	15		
7	Gordon-Friant	18					18	15	15	18	18		
7	Rossi-Stratford	12					12	12	12	12	12		
7	Porterville-Clavicle-Pernu, except	15					15	15	15	15	15		
7	On curves, Success and Pernu branches	12					12	12	12	12	12		
7	Richgrove-Jovista, except	25					25	25	20	25	25		
7	On curves, Richgrove branch	15					15	15	15	15	15		
8	Kern Jct.-M.P. 354½	25					25	25	20	25	25		
8	Mile Post 354½-Olig, except	20					20	15	15	20	20		
8	Mile Post 354-Olig, with large loaded oil cars						15	15	15	15	15		
8	Magunden-Arvin, except	25					25	25	20	25	25		
	On curves, Arvin branch	15					15	15	15	15	15		
8	Mojave-Owenyo, except	30					30	30	20	30	30		
	F-4&F-5 engines-Mojave-Searles						25	25	20	20	25		
8	Over west siding switch, Owenyo	10					10	10	10	10	10		

Speed of 60 miles per hour is permitted gas-electric motor car trains on main track between Fresno and Goshen Jct.

SPEED OF TRAINS REGULATED BY ORDINANCE THROUGH CITY LIMITS

Page	STATION	Passenger	Freight	Running Backward
2-3-7	Fresno, along or across street crossings	20	20	12
2	Fowler, between 5 A. M. and 11 P. M	20	20	20
2	Selma, between 5 A. M. and 11 P. M	20	20	20
2	Kingsburg, between 4 A. M. and 11 P. M	20	20	20
2	Tulare, between 5 A. M. and 11 P. M	20	20	20
3	Reedley, between 5 A. M. and 11 P. M	20	20	20
3	Exeter, between 5 A. M. and 11 P. M	20	20	20

Page	STATION	Passenger	Freight	Running Backward
3	Lindsay, between 5 A. M. and 11 P. M	20	20	20
3	Porterville, between 5 A. M. and 11 P. M	20	20	20
6	Hanford, between 5 A. M. and 11 P. M	20	20	20
6	Armona, Lake Street Crossing	20	20	20
6	Visalia	15	15	15
2-4-8	Bakersfield, within city limits over street crossings	20	20	20

SPEED RESTRICTIONS

Speed restrictions for engines are shown in speed table; however, attention is called to the following maximum speeds at which tenders may be operated subject to restrictions imposed locally:

Tenders having water capacity, 7,000 gallons or less, except classes 70-R-1 and 70-SC-1, maximum speed 50 miles an hour.

Tenders having water capacity in excess of 7,000 gallons, and including classes 70-R-1 and 70-SC-1, maximum speed 60 miles an hour.

Engines operated coupled tender to tender must not exceed speed permitted for light engines of that class running backwards.

Maximum speed of disabled engines hauled in train, or running under own steam, must not exceed:

When pilot removed	20 M.P.H.
When main rod only removed	30 M.P.H.
When side rods only removed	30 M.P.H.
When both main and side rods removed	20 M.P.H.
When hauled in train and all rods are on	30 M.P.H.
GS engines	15 M.P.H.
SP 1, 2 and when inside main rod removed	30 M.P.H.
S and SE engines and all other classes of engines when not equipped with engine trucks	20 M.P.H.
When all weight has been removed from any one pair of drivers on an engine, speed must not exceed	20 M.P.H.
When all weight has been removed from one wheel of any pair drivers on an engine, speed must not exceed	30 M.P.H.

F-2, 3, 4, 5, SP-1, 2, 3, Santa Fe-3800 and AC type engine must not exceed 8 miles per hour backward movement over switch turnout.

When Santa Fe 3800 type engines are used in passenger service their speed is restricted to 45 miles per hour between Bakersfield and M.P. 314.4 and M.P. 359.2 and Mojave and 25 miles per hour between M.P. 330 and M.P. 359.2, other engines not shown in speed table must not exceed freight speed, except MC engines must not exceed 20 miles per hour between Lang and Saugus.

When interlocking signals at Caliente, Allard, Bealville, Woodford and Marcel indicate proceed trains may run at speed and through other interlocking plants with caution.

Trains must not exceed 30 miles per hour through limits of interlocking plant at Calwa Tower.

For speed over Oil Buffer Spring Switches, see list of such switches on Page 10 and be governed by speed given therein.

Through other cross-overs and turnouts trains must not exceed 10 miles per hour.

On sidings in territory between Bakersfield and Saugus trains will run with caution, not exceeding ten miles per hour.

Trains handling relief outfit must not exceed 25 miles per hour between Fresno and Bakersfield, Fresno and Famoso via Sanger, Kerman and Exeter, Bakersfield and one mile west of Ilmon, one mile west of Tehachapi and one mile east of Cameron, Mojave and Mile Post 417, and 20 miles per hour between one mile east of Cameron and Mojave, and must not exceed 15 miles per hour over other track. Where freight speed is less be governed thereby.

When locomotive Cranes, of the type SPMW 3636, are placed in trains, they must be handled with the end forward, except where it is impossible to turn them, in which case they may be turned at the first available point.

In isolated cases, where it becomes absolutely necessary to handle these cranes with the light end forward, extreme care must be exercised and speed of 25 miles per hour not exceeded.

All cars moved in passenger trains must be equipped with steel-tired or all-steel wheels. When cars not so equipped are offered for movement, they will be handled in freight trains—passengers, if any, to move on passenger train.

(a) Wooden passenger-carrying cars, wooden baggage, express and other head-end cars, unless equipped with steel center sills and steel platforms, must not be used in passenger service except upon authority.

(b) Speed of trains handling such cars must be restricted as follows:

When consist includes not more than three wooden passenger-carrying cars, maximum speed must not exceed 50 miles per hour.

When consist includes more than three wooden passenger-carrying cars, maximum speed must not exceed 40 miles per hour.

(c) If consist of train includes both wooden and steel passenger-carrying cars, the wooden cars must be kept together and handled on the rear.

SPECIAL INSTRUCTIONS

SPEED TABLE

Speed per Hour	1 Mile in Min. Sec.	Speed per Hour	1 Mile in Min. Sec.	Speed per Hour	1 Mile in Min. Sec.	Speed per Hour	1 Mile in Min. Sec.
6	10.00	25	2.24	39	1.33	53	1.08
8	7.30	26	2.18	40	1.30	54	1.06
10	6.00	27	2.13	41	1.27	55	1.05
12	5.00	28	2.08	42	1.25	56	1.04
15	4.00	29	2.04	43	1.23	57	1.03
16	3.45	30	2.00	44	1.21	58	1.02
17	3.31	31	1.56	45	1.20	59	1.01
18	3.20	32	1.52	46	1.18	60	1.00
19	3.09	33	1.49	47	1.16	61	0.59
20	3.00	34	1.45	48	1.15	62	0.58
21	2.51	35	1.42	49	1.13	63	0.57
22	2.43	36	1.40	50	1.12	64	0.56
23	2.36	37	1.37	51	1.10	65	0.55
24	2.30	38	1.34	52	1.09		

AVERAGE TARE WEIGHTS OF PASSENGER TRAIN CARS

CLASS	NOT AIR-CONDITIONED		AIR-CONDITIONED	
	All-Steel	Steel Underframe	All-Steel Cooling Season	All-Steel Heating Season
Baggage—60 ft.	93,070			
“ —66 ft.	127,610			
“ —70 ft.	122,620			
“ —70 ft. (With Auto. End Door)	125,800			
“ —(Dynamo)	98,730			
“		87,120		
Baggage & Mail—60 ft.	103,620			
“ “ “ —69 ft.	124,760			
“ “ “ —70 ft.	129,140			
“ “ “		103,590		
“ “ Passenger	108,675	112,640		
Express Refr.—N. P. Ry.		74,000		
“ “ —A. R. E. No. 40–154		78,000		
“ “ — “ “ 155–224		89,000		
“ “ — “ “ 500–506		110,000		
“ “ — “ “ 1101–1175		85,000		
“ “ —P. F. E. “ 500–799		83,000		
Express, Horse	133,050			
Postal	112,120			
Postal Storage—40 ft.	74,530			
“ “ —60 ft.	105,120			
Club	146,210	122,300	160,726	153,710
Official	170,700	155,370		
Chair—60 ft.	100,620		112,985	108,120
“ —74 ft. (Ice Sys.)			180,915	173,125
“ —74 ft. (Steam Ejec. Sys.)			197,944	181,600
Coaches—60 ft.	98,130		110,380	105,630
“ —70 ft.	137,640		151,671	145,140
“ —72 ft.			153,782	147,160
“ —73 ft.			168,245	161,000
“ —72 ft. (Interurban)	120,000			
All-Day Lunch—Chair	105,970			
“ “ —Coach	103,875			
Cafe Coach		138,600	152,675*	146,100*
Diner—70 ft.		135,930		
“ —72 ft.	155,330	146,930		
“ —77 ft. (Arch Type Roof) (Ice Sys.)	156,000		170,857	163,500
“ —77 ft. (Clere Story Roof) (Ice Sys.)		165,530	179,400	171,675
“ —77 ft. (“ “ “) (Mech. Sys.)			189,581	173,836
“ —79 ft.	169,100			
“ —80 ft. (Clere Story Roof) (Mech. Sys.)			201,323	184,700
Cafe Parlor	148,950	161,200	160,198	153,350
Lounge			188,949	180,813
Observation—75 ft.	154,400		169,185	161,900
“ —77 ft.			194,543	186,166
“		141,870		
Pullman-Observation (Ice Sys.)	160,800	153,000	177,314	169,200
“ “ (Mech. Sys.)	160,800	153,000	185,627	170,300
“ “ Lounge (Ice Sys.)	171,200		187,682	179,600
“ “ “ (Mech. Sys.)	171,200		196,963	180,700
“ Bedroom Car (Ice Sys.)	167,600		183,920	176,000
“ “ “ (Mech. Sys.)	167,600		193,039	177,100
“ Sleeper (Ice Sys.)	163,100		180,075	171,500
“ “ (Mech. Sys.)	163,100		188,134	172,600
“ Tourist (Ice Sys.)	153,000		168,663	161,400
“ “ (Mech. Sys.)	153,000		167,625	162,500
Rail Gas-Electric Car, 400 H.P.	158,400			
“ “ “ “ 600 H.P.	167,200			

*Steel Underframe.

STRUCTURES LESS THAN STANDARD CLEARANCE

Mile Post	Location	Description
	Fresno-Saugus—Main Track	
205.5	Fresno Shop Yard	Water tank spout.....Side
205.5	Fresno	Pullman shed.....Side
220.7	Selma	Libby-McNeill & Libby.....Side
313.2	Bakersfield, east end Round House lead	Water column.....Side
313.2	Bakersfield Emergency Column No. 4	Water column.....Side
313.2	Bakersfield, roundhouse turnout tracks	Sandhouse.....Side and Overhead
313.2	Bakersfield	P. F. E. ice dock.....Side
313.2	Bakersfield	Pullman shed.....Side
313.2	Bakersfield	Wheel unloading crane.....Overhead
313.2	Bakersfield	Coal house at store.....Side
313.2	Bakersfield	Air pump house.....Side
313.2	Bakersfield	Gravel Bunkers, Gravel Pit.....Side and Overhead
340.5	Bealville	Water tank spout.....Side
354.2	Marcel	Water tank spout.....Side
434.8	East of Russ	Tunnel 17½.....Overhead
434.8	East of Russ	Water flume.....Overhead
435.5	East of Russ	1st bridge, Santa Clara river.....Side
435.9	East of Russ	3rd bridge, Stanta Clara river.....Overhead
436.1	East of Russ	4th bridge, Santa Clara river...Side and Overhead
436.3	East of Russ	5th bridge, Santa Clara river...Side and Overhead
436.8	East of Russ	7th bridge, Santa Clara river...Side and Overhead
436.9	East of Russ	8th bridge, Santa Clara river...Side and Overhead
437.4	East of Russ	10th bridge, Santa Clara river..Side and Overhead
437.0	East of Russ	Tunnel 18.....Overhead
439.5	East of Lang	Tunnel 20.....Overhead
440.1	East of Lang	Tunnel 21.....Overhead
441.5	East of Lang	Tunnel 22.....Overhead
445.3	East of Humphreys	Tunnel 23.....Overhead
449.7	East of Honby	Tunnel 24.....Overhead
	Fresno-Famoso via Porterville	
205.5	Fresno	S. J. L. & P. Corp. plant.....Side and Overhead
225.3	Fargo	Southern Pacific Freight Shed.....Side
257.4	Exeter	Water tank spout.....Side
	Goshen Jct.-Coalinga-Kerman	
229.1	Armona	Water tank spout.....Side
244.1	Stratford	Water tank spout.....Side
268.4	Coalinga	Water tank spout.....Side
272.0	Leroy	Guy wire and Warehouse.....Side and Overhead
	Fresno-Friant	
205.5	Fresno	Alley Drill Track, Fulton.....Side
217.4	Clovis	Water tank spout.....Side
	Bakersfield-Olig	
328.4	Stevens	Water tank spout.....Side
345.4	Kilowatt	Power House.....Overhead and Side
	Mojave-Owenyo	
402.5	Cantil	Water tank spout.....Side
426.8	West of Searles	Tunnel 29.....Overhead
484.1	Haiwee	Water tank spout.....Side
523.0	Owenyo	Highline trestle on Calif. Alkali Co. Spur.....Overhead and Side

Employes are warned that it is dangerous to ride on top or sides of cars at above-mentioned points. Employes must guard against coming in contact with overhead wires or their connections.

LIST OF SURGEONS

NAME	TITLE	LOCATION
Dr. W. B. Coffey	Manager and Chief Surgeon	San Francisco, Cal.
Dr. J. D. Morgan	District Surgeon	Fresno, Cal.
Dr. Chas. A. James	Asst. District Surgeon	Fresno, Cal.
Dr. D. H. Trowbridge	Oculist and Aurist	Fresno, Cal.
Dr. O. B. Doyle	Asst. District Surgeon	Fresno, Cal.
Dr. J. D. Wagner	Emergency Surgeon	Selma, Cal.
Dr. W. H. Nielson	District Surgeon	Fowler, Cal.
Dr. E. C. Halley	District Surgeon	Sanger, Cal.
Dr. G. A. Hawkins	District Surgeon	Reedley, Cal.
Dr. R. E. Cronemiller	District Surgeon	Exeter, Cal.
Dr. Edgar Brigham	District Surgeon	Dinuba, Cal.
Dr. O. A. Olson	District Surgeon	Kingsburg, Cal.
Dr. M. S. McMurtry	Emergency Surgeon	Clovis, Cal.
Dr. R. N. Fuller	District Surgeon	Tulare, Cal.
Dr. Geo. Dewees	Acting District Surgeon	Tulare, Cal.
Dr. J. Seiberth	District Surgeon	Pixley, Cal.
Dr. Henry A. Rivin	District Surgeon	Delano, Cal.
Dr. W. B. Smith	District Surgeon	Delano, Cal.
Dr. F. R. Guido	District Surgeon	Visalia, Cal.
Dr. C. T. Rosson	District Surgeon	Hanford, Cal.
Dr. J. C. Drake	District Surgeon	Kerman, Cal.
Dr. Geo. A. Meracle	Emergency Surgeon	Caruthers, Cal.
Dr. Wm. P. Byron	District Surgeon	Lemoore, Cal.
Dr. G. T. Mountford	District Surgeon	Coalinga, Cal.
Dr. P. S. Barber	District Surgeon	Porterville, Cal.
Dr. W. W. Tourtillott	Assoc. District Surgeon	Porterville, Cal.
Dr. J. R. Fillmore	Emergency Surgeon	Strathmore, Cal.
Dr. H. D. R. Shoemaker	District Surgeon	Lindsay, Cal.
Dr. H. W. Bell	District Surgeon	Bakersfield, Cal.
Dr. N. N. Brown	Consulting Surgeon	Bakersfield, Cal.
Dr. R. M. Jones	Oculist and Aurist	Bakersfield, Cal.
Dr. E. A. Shaper	District Surgeon	Woodford, Cal.
Dr. Harold L. Schlotthauer	District Surgeon	Tehachapi, Cal.
Dr. C. C. Warner	District Surgeon	Mojave, Cal.
Dr. M. A. Williamson	District Surgeon	Lone Pine, Cal.
Dr. Harvey Crook	District Surgeon	Bishop, Cal.
Dr. B. E. Nicola	District Surgeon	Independence, Cal.
Dr. Thomas A. Drummond	Emergency Surgeon	Randsburg, Cal.
Dr. S. H. Savage	District Surgeon	Lancaster, Cal.
Dr. J. B. Price	District Surgeon	Palmdale, Cal.
Dr. E. C. Innis	District Surgeon	Saugus-Newhall, Cal.
Dr. R. W. Johnson	Assoc. District Surgeon	San Fernando, Cal.

Note.—Emergency Surgeons should only be summoned for temporary treatment when prompt attention is required and when patients cannot be sent to or await arrival of Division or District Surgeon.

LOCATION OF HOSPITAL STRETCHERS

- FRESNO
  - BAGGAGE ROOM
  - STORE ROOM
  - RELIEF TRAIN
- GOSHEN JUNCTION
- BAKERSFIELD
  - BAGGAGE ROOM
  - EMERGENCY HOSPITAL
  - RELIEF TRAIN
  - CAR SHOPS
  - MACHINE SHOPS
- TEHACHAPI
- MOJAVE
  - BAGGAGE ROOM
  - CAR SHOPS
- SAUGUS
- EXETER
- PORTERVILLE
- COALINGA
- HANFORD
- OWENYO

LOCATION OF HOSPITALS

GENERAL HOSPITAL	SAN FRANCISCO
EMERGENCY HOSPITAL	BAKERSFIELD
WHITE MEMORIAL HOSPITAL	LOS ANGELES

RATING OF LOCOMOTIVES--SAN JOAQUIN DIVISION

In M's of 1000 Lbs. Back of Tender.

Nominal Class	Official Class	Engine Numbers	Boiler Pressure	Bakersfield and Fresno via Goshen Jct. Bakersfield and Kerman via Armona. Rosamond, Lancaster. (See note)	Famoso and Fresno, via Exeter	Bakersfield to Mojave	Saugus to Bakersfield	Mojave to Saugus
M-4	M-63 20/28 135-S	1617 to 1713	190	4150	3300	580	680	750
M-4	M-63 20/28 126	1617 to 1713	190	3950	3150	580	670	740
M-8	M-63 21/28 159-S	1721 to 1803	200	4850	3800	700	820	900
M-6	M-63 21/28 150-S							
M-9	M-63 21/28 150-S	1806 to 1822	210	5100	4050	760	890	970
M-11	M-63 21/28 153-S	1831	210	5100	4050	780	910	1000
M-11	M-63 22/28 153-S & 162-SF	1832 to 1835	200	5300	4200	780	910	1000
T-1	T-63 20/26 112	2238 to 2271	180	3550	2800	500	580	640
T-23	T-63 21/28 156-S	2301 to 2310	210	5050	4000	730	850	940
T-23	T-63 21/28 163-SF							
T-28, 31	T-63 22/28 162-S	2311 to 2362	210	5550	4400	820	950	1050
T-32	T-69 23/28 174-S	2363 to 2370, 2372 to 2384	210	5700	4500	860	990	1050
P-1, 3, 5	P-77 22/28 141-S	2400 to 2452, 2459, 2460	210	4600	3600	630	740	800
P-4	P-77 23/28-155/B 58-SF	2400 to 2437	210	5000	3950	690	800	870
P-6	P-77 25/28 172-S	2453 to 2458	200	5650	4450	810	940	1000
P-10	P-73 25/30 181-SF	2478 to 2483	200	6250	4950	830	980	1100
P-10	P-73 25/30-183/B-63-SF	2484 to 2491						
C-9, 10	C-57 22/30 200-SF	2513 to 2599, 2698 to 2860	210	6100	4800	900	1050	1150
C-9, 10	C-57 22/30 194-S							
C-8	C-57 22/30 192-S							
C-5	C-57 22/30 187-S	2624 to 2679						
C-5	C-57 22/30 185-S	2680 to 2693						
A-6	A-81 22/28-127/B-64-SF	3000 to 3003	210	4400	3450	600	690	750
A-3	A-81 20/28 112-S	3025 to 3040, 3043 to 3071	210	3600	2850	450	530	580
A-3	A-81 20/28-116/B-59-S	3025 to 3040, 3043 to 3071						
Mk-5, 6	Mk-63 26/28 210-S	3241 to 3277	210	7800	6200	1200	1350	1500
Mk-5, 6	Mk-63 26/28 231-SF							
Mk-7, 8, 9	Mk-63 29/30 247-S & 257-SF	3300 to 3324	176	8550	6750	1300	1500	1650
F-1	F-63 27½/32 273-S	3611 to 3652	200	8900	7050	1300	1550	1700
F-4, 5	F-63 29½/32-306/B-61-SF	3668 to 3768	200	10,200	8050	1500	1750	1950
F-5	F-63 29½/32-306/B-62-SF							
AC-1, 2, 3	AC-57 $\frac{22-22}{30}$ 441-SF	4000 to 4048	210	12,300	9750	1900	2200	2450
AC-4	AC-63 $\frac{24-24}{32}$ 475-SF	4100 to 4125	235	16,000	12,700	2500	2900	3200
AC-5	AC-63 $\frac{24-24}{32}$ 483-SF							
Mt-1,3,4,5	Mt-73 28/30-246/B-60-SF	4300 to 4376	210	8350	6600	1150	1350	1500
SP-1	SP-63 $\frac{25}{28-32}$ 316/B-60-SF	5000 to 5048	225	12,000	9500	1800	2100	2350
SP-2, 3	SP-63 $\frac{25}{28-32}$ 317/B-61-SF							
Allowance for Empty and Underloaded Cars		Less than 40 Ms.		6	6	3	3	3
		40 Ms. to 50 Ms.		3	3	0	0	0
		More than 50 Ms.		0	0	0	0	0

NOTE—Ratings of thru trains east will be those shown for Mojave to Saugus to avoid filling out at Rosamond.

Ratings of thru trains west will be those shown for Saugus to Bakersfield to avoid filling out at Lancaster.

Main Lines

End Western Division to Goshen Jct.	C. P. Ry.			40.10	
Goshen Jct. to Saugus	S. P. R. R.			211.02	
Fresno to Famoso via Exeter	S. P. R. R.			103.95	
Total Main Lines					355.07

Branches

Arvin	S. P. Co.	Magunden to Arvin		16.89	
McKittrick	S. P. R. R.	Bakersfield to Olig		50.07	
Clovis	S. P. R. R.	Fresno to Friant		24.14	
Coalinga	S. P. R. R.	Armona to Crump		43.08	
Fresno Interurban	F. I. Ry.	Barton Transfer to Hammond	2.29		
		Barton Transfer to Belmont Ave.	14.60	16.89	
Kerman	S. P. R. R.	Kerman to Goshen Jct. via Armona		51.37	
Minkler Southern	A.T.&S.F.Ry.	Porterville to Ducor		12.53	
Oil City	S. P. R. R.	Oil Junction to Oil City		6.76	
Owenyo	C. P. Ry.	Mojave to Owenyo		143.15	
Pernu	S. P. Co.	Pernu Junction to Pernu		1.48	
Richgrove	S. P. R. R.	Richgrove to Jovista		4.16	
Riverdale	S. P. R. R.	Hardwick to Ingle		42.15	
Success	S. P. Co.	Porterville (Olive St.) to Clavicle		13.44	
Stratford	S. P. R. R.	Rossi to Stratford		8.26	
Visalia	S. P. R. R.	Goshen Junction to Exeter		16.76	
Total Branches					451.13
Total San Joaquin Division					806.20

These ratings include the total weight of train, exclusive of engine and tender, which the different class of locomotives will haul in each direction between the stations shown.

CLASS "C"—Consolidation engine "M"—Moguls "Mk"—Mikado "E"—Eight-wheeler
"T"—Ten-wheelers "TW"—Twelve-wheelers "P"—Pacific Type

Example:—Consolidation engine having 57-inch drivers, Cylinders 22-inch diameter and 30-inch stroke, and weighing 187,000 pounds on Drivers: C-57 $\frac{22}{30}$ 187

C. G. TANDY, Trainmaster, Fresno
A. H. HOFFMAN, Trainmaster and Road Foreman of Engines, Mojave

E. F. WASEM, Chief Dispatcher,
P. E. TURNER, Asst. Chief Dispatcher,
J. S. FOCKLER, Asst. Chief Dispatcher.

L. P. HOPKINS, Asst. Superintendent.


CALIFORNIA
MADERA
FRESNO
TULARE
KINGS
KERN
INYO
SAN BERNARDINO
LOS ANGELES
SAN LUIS OBISPO
SANTA BARBARA
MONTEREY
NEVADA
PACIFIC OCEAN
TULARE LAKE
COALINGA OIL FIELDS
KETTLEMAN OIL FIELDS
KERN RIV. OIL FIELDS
MCKITTRICK OIL FIELDS
SUNSET OIL FIELDS
SAN EMIDIO MTS.
WHEELER RIDGE
SEQUOIA NATIONAL PARK
SEQUOIA NATIONAL FOREST
KERN NATIONAL FOREST
ANGELES MADRE NATIONAL FOREST
SAN LUIS NATIONAL FOREST
SANTA BARBARA NATIONAL FOREST
MONTEREY NATIONAL FOREST
GENERAL GRANT NAT. PARK
GIANT FOREST
KAWEAH PEAKS
MT. WHITNEY HIGHEST MT. IN THE U.S. 14,501 Ft.
BRECKENRIDGE MT. 7544 Ft.
BEAR MT. 6934 Ft.
TEHACHAPI Summit Elev. 4025 Ft.
TULE RIVER INDIAN RESERVE
Death Valley
OWENS LAKE
FRESNO
BAKERSFIELD
KERN JCT.
MOJAVE
LOS ANGELES
SAUGUS
SEARLES
OWENYO
KEELER
VISALIA
HANFORD
GOSHEN JCT.
PORTERVILLE
EXETER
SAN LUIS OBISPO
N.
FRESNO AND ADJACENT TERRITORY
SCALE OF MILES
0 1 2 3 4 5 10 15 20

MAP OF THE SAN JOAQUIN DIVISION

SOUTHERN PACIFIC COMPANY

JUNE, 1918.

J. F. M.

SCALE OF MILES

0 5 10 20 30 40

REVISED. OCT. 6, 1928
" JAN. 1, 1929
" JULY 15, 1929
" JAN. 1, 1930.
" FEB. 13, 1930.
" JULY 7, 1930.
" JAN 1, 1931.